

ネボﾝ株式会社

【ハウスオキ 17, 22型シリーズ】

2015年度 (平成 27 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						1995		1996		1997			
											%	(l/h)	%	(l/h)	%	(l/h)		
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			85.6%	5.1	85.8%	5.0	86.1%	5.0	
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			85.6%	5.1	85.8%	5.0	86.1%	5.0	
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			85.6%	5.1	85.8%	5.0	86.1%	5.0	
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			85.6%	5.1	85.8%	5.0	86.1%	5.0	
			HK1522TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形			85.6%	5.1	85.8%	5.0	86.1%	5.0
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形			85.6%	5.1	85.8%	5.0	86.1%	5.0
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形			85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形			85.6%	6.7	85.8%	6.6	86.1%	6.6
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9~13.2				85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2~16.5				85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				85.6%	16.6	85.8%	16.6	86.1%	16.6
HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			85.6%	16.6	85.8%	16.6	86.1%	16.6			
HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			85.6%	16.6	85.8%	16.6	86.1%	16.6			
HK5017TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				85.6%	16.6	85.8%	16.6	86.1%	16.6			
HK6022TC	150,000	174	19.0	90.0%	A重油	16.5~19.8				85.6%	20.0	85.8%	19.9	86.1%	19.9			
HK6022TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				85.6%	20.0	85.8%	19.9	86.1%	19.9			
HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			85.6%	20.0	85.8%	19.9	86.1%	19.9			
HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			85.6%	20.0	85.8%	19.9	86.1%	19.9			
HK6017TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				85.6%	20.0	85.8%	19.9	86.1%	19.9			
HK8022TF	200,000	233	19.0	90.0%	A重油	19.8~26.4				85.6%	26.6	85.8%	26.6	86.1%	26.5			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											4.9%		4.6%		4.4%			