

ネボン株式会社

【ハウスオンキ 24型シリーズ】

2015年度 (平成 27 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3024TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK4024TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 50Hz	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 60Hz	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4024TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK5024TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5024TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5024TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5024TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5024TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5024TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK6024TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.8%	19.9	86.0%	19.9	86.2%	19.8
			HK6024TE	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.8%	19.9	86.0%	19.9	86.2%	19.8
HK6024TF	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6024TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6024TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6024TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.8%	19.9	86.0%	19.9	86.2%	19.8			
現行機種 (機器熱効率 90% )へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										4.7%		4.4%		4.2%		