

ネボン株式会社
【ハウスオナキ 23型シリーズ】

2013 年度 (平成 25 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量												
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005		
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形		85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9~13.2			85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9~13.2			85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9~13.2			85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形		85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2			85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2~16.5			85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2~16.5			85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2~16.5			85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5023TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5
			HK6023TC	150,000	174	19.4	88.0%	A重油	16.5~19.8			85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8
			HK6023TE	150,000	174	19.4	88.0%	A重油	16.5~19.8			85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8
HK6023TF	150,000	174	19.4	88.0%	A重油	16.5~19.8			85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6023TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8			
HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											5.4%	5.1%	4.9%	4.7%	4.4%	4.2%							