

ネボン株式会社

【ハウスナキ 8,10型シリーズ】

2013年度 (平成 25 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																			
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988									
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)								
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95		81.4%	4.5	81.6%	4.5	81.9%	4.5														
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95		81.4%	4.5	81.6%	4.5	81.9%	4.5														
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		81.4%	7.0	81.6%	7.0	81.9%	7.0														
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		81.4%	7.0	81.6%	7.0	81.9%	7.0														
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		81.4%	10.5	81.6%	10.5	81.9%	10.4														
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		81.4%	10.5	81.6%	10.5	81.9%	10.4														
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		81.4%	10.5	81.6%	10.5	81.9%	10.4														
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		81.4%	10.5	81.6%	10.5	81.9%	10.4														
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		81.4%	10.5	81.6%	10.5	81.9%	10.4														
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2		81.4%	12.2	81.6%	12.1	81.9%	12.1														
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2		81.4%	12.2	81.6%	12.1	81.9%	12.1														
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2		81.4%	12.2	81.6%	12.1	81.9%	12.1														
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		81.4%	17.5	81.6%	17.5	81.9%	17.4														
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		81.4%	21.0	81.6%	20.9	81.9%	20.9														
			10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4						
HK160SC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4									
HK160TE	32,000	37.2				4.2	88.0%	A重油	3.3~4.95					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4									
HK160TC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4									
HK160TEP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95	静音形					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4								
HK160TCP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95	静音形					81.9%	4.5	82.1%	4.4	82.3%	4.4	82.5%	4.4								
HK210SE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6						81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK210SC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6						81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK210TE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6						81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK210TC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6						81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK210TEP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6	静音形					81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK210TCP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6	静音形					81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9								
HK310SE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9						81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310SC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9						81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9						81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9						81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TEP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9	静音形					81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TCP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9	静音形					81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TCM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9	システムナ					81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TEM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9	システムナ					81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK310TFM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9	システムナ					81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4								
HK410TE	87,000	101				11.3	88.0%	A重油	9.9~13.2						81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TC	87,000	101				11.3	88.0%	A重油	9.9~13.2						81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TEP	87,000	101				11.3	88.0%	A重油	9.9~13.2						81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TCP	87,000	101				11.3	88.0%	A重油	9.9~13.2	静音形					81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TCM	87,000	101				11.3	88.0%	A重油	9.9~13.2	システムナ					81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TEM	87,000	101				11.3	88.0%	A重油	9.9~13.2	システムナ					81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK410TFM	87,000	101				11.3	88.0%	A重油	9.9~13.2	システムナ					81.9%	12.1	82.1%	12.1	82.3%	12.1	82.5%	12.0								
HK510TC	125,000	145				16.2	88.0%	A重油	13.2~16.5						81.9%	17.4	82.1%	17.4	82.3%	17.3	82.5%	17.3								
HK510TEP	125,000	145				16.2	88.0%	A重油	13.2~16.5	静音形					81.9%	17.4	82.1%	17.4	82.3%	17.3	82.5%	17.3								
HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5	システムナ					81.9%	17.4	82.1%	17.4	82.3%	17.3	82.5%	17.3											
HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8						81.9%	20.9	82.1%	20.8	82.3%	20.8	82.5%	20.7											
HK610TEP	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形					81.9%	20.9	82.1%	20.8	82.3%	20.8	82.5%	20.7											
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8	システムナ					81.9%	20.9	82.1%	20.8	82.3%	20.8	82.5%	20.7											
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4						81.9%	27.9	82.1%	27.8	82.3%	27.7	82.5%	27.6											
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											9.5%	9.3%	9.0%	8.8%	8.6%	8.3%														