ネ	ポ	 株式会社

1187 1007 59.000 59.1 6.4 90.00 Agia 4, 485-6.0 44.5% 6.7 84.7% 6.7 85.7% <th></th> <th>ン 株式 わキ 11,</th> <th></th> <th>望シリース゛】</th> <th>2013 4</th> <th>年度</th> <th>(平成</th> <th>25</th> <th>年度)</th> <th>熱効率/燃</th> <th>料消費量</th> <th>経年変化一覧</th> <th>表</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>		ン 株式 わキ 11,		望シリース゛】	2013 4	年度	(平成	25	年度)	熱効率/燃	料消費量	経年変化一覧	表							
Pire Pire Desire Tim Desire Tim Desire	制品	制造	制法	il Mt																
Unit Unit <thunit< th=""> Unit Unit <thu< th=""><th></th><th></th><th></th><th>製品型式</th><th></th><th></th><th colspan="2"></th><th></th><th>備考</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></thu<></thunit<>				製品型式							備考									
Integrate Bit 200																				
HS12000 88.000 44.2 4.8 0.9 A 28 5.1 84.3 5.1 85.4																				
Integra Bit 13000 Bit 2000																				
Interview Interview <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>																				
Interview No. No. No. No. No											静音形									
Image: bit with the second state in the sec																				
Integrate Integrate <t< td=""><td></td><td></td><td>HK2020SC</td><td>50,000</td><td>58.1</td><td>6.4</td><td></td><td></td><td></td><td></td><td></td><td></td><td>84.7% 6.7</td><td></td><td></td><td>85.4% 6.7</td><td></td><td>85.8% 6.6</td><td>86.1% 6.6</td></t<>				HK2020SC	50,000	58.1	6.4							84.7% 6.7			85.4% 6.7		85.8% 6.6	86.1% 6.6
Image: relation of the state is a state in the state is a state state state is a state is a state state state is a state				HK2020SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		84.3% 6.8	84.5% 6.7	84. 7% 6. 7	85.0% 6.7	85.2% 6.7	85.4% 6.7	85.6% 6.7	85.8% 6.6	86.1% 6.6
Image: start Mark control Solution																				
Image: Note of the second se																				
112 100 6.0 <td></td>																				
11 1 90 0.81 1.64 90.0 A 28 1.6 94.75 1.7 85.76 6.7 85.24 1.0 85.44 1.0 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 85.44 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>																				
112 113 100 0.7 0.5 0.0 0.7 0.5 0.0 0.7 0.5 0.0 0.7 0.5 0.0 0.7 <td></td>																				
Integrate No.0167 77. 000 67.2 6.5 0.0 8.4.7 10.0 85.4 10.0											月子 日 ハシ									
112 1037 15:00 87.2 5.5 90.0 8.2 mm 6.8 mm 10.1 84.3 10.1 84.5 10.1 85.7 10.0 85.6																				
Instrument Bit is a structure Bit is a struct																				
112 113 115 100 65.2 10.0 65.2 10.0 65.4 10.0 65.6 10.0 65.15 10.0 65.15 10.0 65.15 10.0 65.15 10.0 65.4 10.0 65.6 10.0 65.15 10.0 65.15 10.0 65.55					· · · · · · · · · · · · · · · · · · ·															
118 118 119 119 110 15 10 0 0 <t< td=""><td></td><td></td><td></td><td>HK3020TC</td><td>75,000</td><td>87.2</td><td>9.5</td><td>90.0%</td><td>A重油</td><td>6.6~9.9</td><td></td><td>84. 3% 10. 1</td><td>84.5% 10.1</td><td>84. 7% 10. 1</td><td>85.0% 10.1</td><td>85.2% 10.0</td><td>85.4% 10.0</td><td>85.6% 10.0</td><td>85.8% 10.0</td><td>86.1% 9.9</td></t<>				HK3020TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84. 3% 10. 1	84.5% 10.1	84. 7% 10. 1	85.0% 10.1	85.2% 10.0	85.4% 10.0	85.6% 10.0	85.8% 10.0	86.1% 9.9
Intro Protection Protection </td <td></td>																				
112 113 <td></td>																				
112 195 195 10.0 A 2 9 9 9 8 4.33 10.1 84.55 10.1 85.55 10.0 85.45 10.0 <																				
118/1 118/2 1007 17.5 00 17.2 9.5 90.0 A 28 is 6.9-9 P##5/5 44.35 10.1 84.75 10.1 85.75 10.0 85.65 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>																				
Inst Inst Inst Inst Inst Inst Inst Inst																				
Hig Hig <td></td>																				
1987 15世 20型 1987 (107) 1997 (107) 110 (107) 000 (107) 14 ± 10 000 (107) 14 ± 10 110 000 (107) 14 ± 10 110 000 (107) 14 ± 10 110 110 <td></td>																				
1987 (952) 1987 (952) 108 (957) 1080 (957) 1080 (957) 1080 (957) 1080 (95	11型		1005		75,000	87.2		90.0%	A重油	6.6~9.9		84. 3% 10. 1	84.5% 10.1	84. 7% 10. 1		85. 2% 10. 0			85.8% 10.0	86.1% 9.9
1920 (SE2) (NT) mS20110 51,000 81.2 9.2 97/24.8 84.3 10.1 64.5 10.0 65.2 10.0 65.2 15.0 85.5 10.0 65.2 10.0 10.0 65.0 10.0 65.0 10.0 10.0 10.0 10.0	•	1987																		
202 Wet0157C 87,000 101 11.0 900% A maile 9-13.2 84.3% 11.8 84.5% 11.7 94.7% 11.7 85.0% 11.7 85.2% 11.6 85.4% 11.6 85.6% 11.6	15型	(\$62)									デラックス形									
Image: Section 11 10 000 1 11 000 11 10 000 1 11 000 11 10 000 11 10 000 11 10 000 11 10 000 11 10 100 11 <td< td=""><td>· 20型</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	· 20型																			
HK4020TC 87,000 101 11.0 90,0% A 運油 9 9~13.2 84.3% 11.8 84.5% 11.7 85.0% 11.7 85.0% 11.6 85.6% 11.7 84.7% 11.7 85.0% 11.7 85.7% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6%																				
HK402DTE 87.000 101 11.0 90.0% A ## 3 93.2 94.3% 11.8 84.7% 11.7 85.0% 11.6 85.4% 11.6 85.6% <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>																				
HK4020TF 87,000 101 11.0 90.0% A 重油 9.9-13.2 特音形 84.3% 11.8 84.5% 11.7 84.7% 11.7 85.0% 11.6 85.6% 11.6																				
H#4020TEP 87,000 101 11.0 90.0% A 重油 9.9~13.2 静音形 84.3% 11.8 84.5% 11.7 85.0% 11.7 85.0% 11.6 85.6% 11.6				HK4020TF	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.3% 11.8	84.5% 11.7	84.7% 11.7	85.0% 11.7	85.2% 11.6	85.4% 11.6	85.6% 11.6	85.8% 11.6	86.1% 11.5
HK4020TFP 97.000 101 11.0 90.0% A 重油 9.9-13.2 静音形 84.3% 11.8 84.5% 11.7 85.0% 11.7 85.2% 11.6 85.6% 11.6																				
HK4020TCS 87.000 101 11.0 90.0% ▲重油 9.9~13.2 静音形 84.3% 11.7 84.7% 11.7 85.0% 11.6 85.6% 11.6																				
HK4020TES 87,000 101 11.0 90.0% A 董油 9.9~13.2 静音形 84.3% 11.8 84.5% 11.7 84.7% 11.7 85.0% 11.6 85.4% 11.6 85.6% 11.6 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>																				
HK4020TFS 87.000 101 11.0 90.% ▲重油 9.9~13.2 静音形 84.3% 11.7 84.7% 11.7 85.2% 11.6 85.2% 11.6 85.6% 11.6																				
HK4020TC0 87,000 101 11.0 90.0% A 重油 9.9~13.2 7*772/37 84.3% 11.8 84.5% 11.7 84.7% 11.7 85.0% 11.6 85.4% 11.6 85.6% 16.6 85.6% 16.6 <td></td>																				
HK4020TFD 87,000 101 11.0 90.0% A 重曲 9.9~13.2 デッカ形形 84.3% 11.7 85.0% 11.7 85.0% 11.7 85.0% 11.7 85.0% 11.7 85.0% 11.7 85.0% 11.7 85.0% 11.6 85.6% 11.6 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.6% 16.6 85.6% 16.6							*****													
HK4011T0E 87.000 101 11.0 90.0% A 重油 9.9~13.2 84.3% 11.8 84.5% 11.7 85.0% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 11.6 85.6% 16.6 85.6%				HK4020TED	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形	84.3% 11.8	84.5% 11.7	84.7% 11.7	85.0% 11.7	85.2% 11.6	85.4% 11.6	85.6% 11.6	85.8% 11.6	86.1% 11.5
HK50157C 125.000 145 15.8 90.0% A 重油 13.2~16.5 84.3% 16.9 84.7% 16.8 85.0% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.6%				HK4020TFD	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形	84.3% 11.8	84.5% 11.7	84.7% 11.7		85.2% 11.6	85.4% 11.6		85.8% 11.6	86.1% 11.5
HK5020TC 125,000 145 15.8 90.0% A 重油 13.2~16.5 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8%																				
HK5020TCP 125,000 145 15.8 90.0% A重油 13.2~16.5 静音形 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 86.1% 16.6 HK5020TCS 125,000 145 15.8 90.0% A重油 13.2~16.5 静音形 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 86.1% 16.6 HK5020TCD 125,000 145 15.8 90.0% A重油 13.2~16.5 静音形 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 86.1% 16.6 HK5020TCD 150,000 174 19.0 90.0% A重油 13.2~16.5 デアシス形 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 86.1% 16.6 HK501TCE 150,000 174 19.0 90.0% A重油 16.5~19.8 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.4% 10.7 85.6% 16.6 85.8% 16.6 86.1% 19.9 HK6020TCP 150,000 174 19.0 90.0% A重油 16.5~19.8 84.3% 10.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 持7572.8 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.1 85.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 HK6020TCD 150,000 174 1																				
HK5020TCS 125.000 145 15.8 90.0% A 重油 13.2~16.5 静音形 84.3% 16.9 84.7% 16.8 85.0% 16.7 85.4% 16.7 85.6% 16.6 85.8% 16.6 86.1% 16.6 HK5020TCD 125.000 145 15.8 90.0% A 重油 13.2~16.5 797/N 84.3% 16.9 84.7% 16.8 85.0% 16.8 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.6 85.2% 16.7 85.6% 16.6 85.6% 16.8 85.6% 16.7 85.6% 16.6 85.6% 16.8 85.6% 16.8 85.6% 16.7 85.6% <td rowspan="5"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>林 立 11/</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>											林 立 11/									
HK5020TC0 125.000 145 15.8 90.0% A 重油 13.2~16.5 デッア2形 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.7 85.6% 16.6 85.6% 16.6 85.6% 16.6 85.6% 16.6 85.6% 16.6 85.6% 16.6 85.6% 16.7 85.6% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.2% 16.7 85.6% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.6 85.8% 16.8 85.2% 16.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7 85.4% 10.7																				
HK5011TCE 125.000 145 15.8 90.0% A 重油 16.5 84.3% 16.9 84.5% 16.9 84.7% 16.8 85.0% 16.7 85.6% 16.6 95.6% 16.6 95.6% 16.6 95.6% 16.7 85.6% 16.7 85.6% 16.6 95.8% 16.6 95.8% 16.6 95.6% 16.7 85.6% 16.7 85.6% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.6 95.8% 16.7 95.4% 20.0 85.6% 20.0 85.8% 19.9 86.1% 19.9 94.3% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.6% 20.0 85.8% 19.9 86.1% 19.9 94.3% 20.3 84.3% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.8% 20.0 85.8% 19.9 86.1% <th< td=""><td rowspan="2"></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></th<>																				
HK6015TC 150.000 174 19.0 90.0% A 重油 16.5~19.8 84.3% 20.3 84.5% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6%											1 11111									
HK6020TCC 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK6020TCP 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 神音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK6020TCD 150,000 174 19.0 90.0% A重油 16.5~19.8 神音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 16.5~19.8 神音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 16.5~19.8 神音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 16.5~19.8 #84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 19.8~24 48.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 19.8~264 84.3% 27.0 84.5% 27.0 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 85.8% 19.9 86.1% 19.9 HK601TCE 150,000 174 19.0 90.0% A重油 19.8~264 84.3% 27.0 84.5% 27.0 84.7% 20.2 85.0% 20.1 85.2% 20.1 85.4% 20.0 85.6% 20.0 85.6% 20.6 85.6%																				
HK6020TCS 150,000 174 19.0 90.0% A 重油 16.5~19.8 静音形 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.0 85.6% 20.1 85.6% 20.1 85.6% 20.0				HK6020TC																
HK6020TCD 150,000 174 19.0 90.0% A 重油 16.5~19.8 デ プッカル形 84.3% 20.3 84.5% 20.2 85.0% 20.1 85.4% 20.0 85.6% 20.0 </td <td></td>																				
HK6011TCE 150,000 174 19.0 90.0% A 重油 16.5~19.8 84.3% 20.3 84.5% 20.2 84.7% 20.2 85.0% 20.1 85.4% 20.0 85.6% <td></td>																				
HK8020TC 200,000 233 25.3 90.% A 重油 19.8~26.4 84.3% 27.0 84.5% 26.9 85.0% 26.8 85.4% 26.7 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 85.6% 26.6 86.1% 26.5 現行機種 (機器熟効率 90%) <hr/> <hr/> 6 3% 6 1% 5.8% 5.6% 5.4% 5.1% 4.9% 4.6% 4.4%											エ ラックスポジ									
現行機種(機器熱効率 90%)へ設備更新した場合の 6.1% 5.8% 5.6% 5.4% 5.1% 4.0% 4.6% 4.4%																				
	L						r													
									0.3%	b. 1%	5.8%	5.6%	5.4%	5.1%	4.9%	4. 0%	4.4%			