

ネボン株式会社  
【ハウスホネキ 25Z型シリーズ】

2013年度 (平成 25年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																			
				kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7		
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TR5Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9		
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1		
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4		
			HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4		
			HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4		
			HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4		
			HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4		
HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4					
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.9%	3.7%	3.4%	3.2%	2.9%	2.7%	2.4%	2.2%	1.9%											