## ネ ポ ン 株式会社

	ン 株式 オンキ 25.		シリース゛】	2013	年度	(平成	25	年度)	勢効率/物	料消費量 経年	変化一覧表								
製品シリース		製造	製品型式			燃料	熱効率		標準暖房 面積(a)	備考		製造年度別 経年変化による現在の熱効率および燃料消費量							
	製造 開始年			熱出力		消費量					1997	1998	1999	2000	2001	2002	2003	2004	2005
,, n	17074	4-11		(kcal/h)		(I/h)					% (I/h)	% (I/h		% (I/h)					
			HK1525SC	38, 000	44. 2	4. 9	88.0%	A重油			84.5% 5.1	84. 7% 5. 1		85. 2% 5. 1	85. 4% 5. 1	85. 6% 5. 1	85. 8% 5. 0 85. 8% 5. 0	86.0% 5.0	86. 2% 5. 0
			HK1525SE HK1525TC	38, 000 38, 000	44. 2 44. 2		88. 0% 88. 0%	A 重油	3. 3~4. 95 3. 3~4. 95		84. 5% 5. 1 84. 5% 5. 1	84. 7% 5. 1 84. 7% 5. 1		85. 2% 5. 1 85. 2% 5. 1	85. 4% 5. 1 85. 4% 5. 1	85. 6% 5. 1 85. 6% 5. 1	85. 8% 5. 0 85. 8% 5. 0	86.0% 5.0 86.0% 5.0	86. 2% 5. 0 86. 2% 5. 0
			HK1525TE	38, 000	44. 2	4. 9	88.0%		3.3~4.95		84.5% 5.1	84. 7% 5. 1		85. 2% 5. 1	85. 4% 5. 1	85.6% 5.1	85.8% 5.0	86.0% 5.0	86. 2% 5. 0
			HK1525TCP	38, 000	44. 2	4. 9	88.0%		3.3~4.95	静音形	84. 5% 5. 1	84. 7% 5.		85. 2% 5. 1	85. 4% 5. 1	85. 6% 5. 1	85. 8% 5. 0	86.0% 5.0	86. 2% 5. 0
			HK1525TEP	38, 000	44. 2	4. 9	88. 0%	A重油		静音形	84. 5% 5. 1	84. 7% 5. 1		85. 2% 5. 1	85. 4% 5. 1	85. 6% 5. 1	85. 8% 5. 0	86.0% 5.0	86. 2% 5. 0
			HK2025SC	50, 000	58. 1	6. 5	88.0%	A重油	4.95~6.6		84. 5% 6. 7	84. 7% 6. 7	84. 9% 6. 7	85. 2% 6. 7	85. 4% 6. 7	85. 6% 6. 7	85. 8% 6. 6	86.0% 6.6	86. 2% 6. 6
			HK2025SE	50, 000	58. 1		88.0%		4.95~6.6		84. 5% 6. 7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85. 6% 6. 7	85. 8% 6. 6	86.0% 6.6	86. 2% 6. 6
			HK2025SR	50, 000	58. 1		88.0%		4.95~6.6		84. 5% 6. 7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85. 6% 6. 7	85.8% 6.6	86.0% 6.6	86. 2% 6. 6
			HK2025TC	50, 000	58. 1		88.0%		4.95~6.6		84. 5% 6. 7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85. 6% 6. 7	85. 8% 6. 6	86.0% 6.6	86. 2% 6. 6
			HK2025TE	50, 000	58. 1	6.5	88.0%		4.95~6.6	7 /2 h* T/	84.5% 6.7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85.6% 6.7	85.8% 6.6	86.0% 6.6	86. 2% 6. 6
			HK2025TR HK2025TCS	50, 000 50, 000	58. 1 58. 1	6.5	88. 0% 88. 0%	A 重油	4. 95~6. 6 4. 95~6. 6	スイング形 静音形	84. 5% 6. 7 84. 5% 6. 7	84. 7% 6. 7 84. 7% 6. 7		85. 2% 6. 7 85. 2% 6. 7	85. 4% 6. 7 85. 4% 6. 7	85. 6% 6. 7 85. 6% 6. 7	85. 8% 6. 6 85. 8% 6. 6	86.0% 6.6 86.0% 6.6	86. 2% 6. 6 86. 2% 6. 6
			HK2025TES	50, 000	58. 1	6. 5	88.0%	A重油		静音形	84.5% 6.7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85.6% 6.7	85.8% 6.6	86.0% 6.6	86. 2% 6. 6
			HK2025TES	50, 000	58. 1		88.0%		4. 95~6. 6	静音形	84. 5% 6. 7	84. 7% 6. 7		85. 2% 6. 7	85. 4% 6. 7	85.6% 6.7	85. 8% 6. 6	86.0% 6.6	86. 2% 6. 6
			HK3025SC	75, 000	87. 2		88. 0%		6.6~9.9		84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025SE	75, 000	87. 2	9. 7	88.0%	A重油	6.6~9.9		84. 5% 10. 1	84. 7% 10. 1	84. 9% 10. 1	85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85.8% 10.0	86.0% 9.9	86. 2% 9. 9
			HK3025SR	75, 000	87. 2		88.0%	A重油		スイング形	84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025TC	75, 000	87. 2	9. 7	88.0%	A重油			84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025TE	75, 000	87. 2	9. 7	88.0%	A重油			84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025TF	75, 000	87. 2		88.0%			7 /2 h* T/	84.5% 10.1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85.6% 10.0	85.8% 10.0	86.0% 9.9	86. 2% 9. 9
			HK3025TR HK3025TCS	75, 000 75, 000	87. 2 87. 2		88. 0% 88. 0%		6.6~9.9 6.6~9.9	スイング形 静音形	84. 5% 10. 1 84. 5% 10. 1	84. 7% 10. 1 84. 7% 10. 1		85. 2% 10. 0 85. 2% 10. 0	85. 4% 10. 0 85. 4% 10. 0	85. 6% 10. 0 85. 6% 10. 0	85. 8% 10. 0 85. 8% 10. 0	86.0% 9.9 86.0% 9.9	86. 2% 9. 9 86. 2% 9. 9
			HK3025TES	75, 000	87. 2		88.0%		6.6~9.9	静音形	84. 5% 10. 1	84. 7% 10.		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85.8% 10.0	86.0% 9.9	86. 2% 9. 9
			HK3025TFS	75, 000	87. 2	9. 7	88.0%		6.6~9.9	静音形	84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025TCE	75, 000	87. 2		88. 0%	A重油			84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
			HK3025TEE	75, 000	87. 2	9. 7	88.0%	A重油	6.6~9.9		84. 5% 10. 1	84. 7% 10. 1	84. 9% 10. 1	85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
25 #1			HK3025TFE	75, 000	87. 2		88.0%		6.6~9.9		84. 5% 10. 1	84. 7% 10. 1		85. 2% 10. 0	85. 4% 10. 0	85. 6% 10. 0	85. 8% 10. 0	86.0% 9.9	86. 2% 9. 9
25型 • 25E型	1997	2005	HK4025TC	100, 000		13. 0	88.0%		9.9~13.2		84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4		85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
	(H9)	(H17)	HK4025TE	100, 000	116		88.0%		9.9~13.2		84.5% 13.5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TF HK4025TR5	100, 000 100, 000	116 116		88. 0% 88. 0%	A 重油	9.9~13.2 9.9~13.2	スインク* 形, 50Hz	84. 5% 13. 5 84. 5% 13. 5	84. 7% 13. 5 84. 7% 13. 5		85. 2% 13. 4 85. 2% 13. 4	85. 4% 13. 4 85. 4% 13. 4	85. 6% 13. 3 85. 6% 13. 3	85. 8% 13. 3 85. 8% 13. 3	86. 0% 13. 3 86. 0% 13. 3	86. 2% 13. 2 86. 2% 13. 2
			HK4025TR5	100, 000	116		88.0%		9.9~13.2	スインケ 形, 50Hz スインケ 形, 60Hz	84.5% 13.5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TCS	100, 000	116		88.0%		9.9~13.2	静音形	84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TES	100, 000	116		88.0%		9.9~13.2	静音形	84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TFS	100, 000	116		88.0%		9.9~13.2	静音形	84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TRS	100, 000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84. 5% 13. 5	84. 7% 13. 5	84. 9% 13. 4	85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TCE	100, 000	116		88.0%		9.9~13.2		84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
1			HK4025TEE	100, 000	116		88.0%		9.9~13.2		84. 5% 13. 5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK4025TFE	100, 000	116		88. 0%		9.9~13.2		84.5% 13.5	84. 7% 13. 5		85. 2% 13. 4	85. 4% 13. 4	85. 6% 13. 3	85. 8% 13. 3	86.0% 13.3	86. 2% 13. 2
			HK5025TC HK5025TE	125, 000 125, 000	145 145		88. 0% 88. 0%		13. 2~16. 5 13. 2~16. 5		84. 5% 16. 9 84. 5% 16. 9	84. 7% 16. 8 84. 7% 16. 8		85. 2% 16. 7 85. 2% 16. 7	85. 4% 16. 7 85. 4% 16. 7	85. 6% 16. 6 85. 6% 16. 6	85. 8% 16. 6 85. 8% 16. 6	86.0% 16.6 86.0% 16.6	86. 2% 16. 5 86. 2% 16. 5
1			HK5025TE	125, 000	145		88.0%		13. 2~16. 5		84.5% 16.9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85. 6% 16. 6	85.8% 16.6	86.0% 16.6	86. 2% 16. 5
		l	HK5025TCS	125, 000	145		88.0%		13. 2~16. 5	静音形	84. 5% 16. 9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85. 6% 16. 6	85. 8% 16. 6	86.0% 16.6	86. 2% 16. 5
		l	HK5025TES	125, 000	145		88.0%	A重油			84.5% 16.9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85.6% 16.6	85.8% 16.6	86.0% 16.6	86. 2% 16. 5
			HK5025TFS	125, 000	145	16. 2	88.0%	A重油	13.2~16.5	静音形	84. 5% 16. 9	84. 7% 16. 8	84. 9% 16. 8	85. 2% 16. 7	85. 4% 16. 7	85. 6% 16. 6	85. 8% 16. 6	86.0% 16.6	86. 2% 16. 5
			HK5025TCE	125, 000	145		88.0%		13. 2~16. 5		84. 5% 16. 9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85. 6% 16. 6	85. 8% 16. 6	86.0% 16.6	86. 2% 16. 5
		l	HK5025TEE	125, 000	145		88.0%		13. 2~16. 5		84. 5% 16. 9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85. 6% 16. 6	85. 8% 16. 6	86.0% 16.6	86. 2% 16. 5
		l	HK5025TFE	125, 000	145		88.0%		13. 2~16. 5		84.5% 16.9	84. 7% 16. 8		85. 2% 16. 7	85. 4% 16. 7	85.6% 16.6	85.8% 16.6	86.0% 16.6	86. 2% 16. 5
		l	HK6025TC	150, 000 150, 000	174 174		88. 0% 88. 0%		16.5~19.8		84. 5% 20. 2 84. 5% 20. 2	84. 7% 20. 2 84. 7% 20. 2		85. 2% 20. 1 85. 2% 20. 1	85. 4% 20. 0 85. 4% 20. 0	85. 6% 20. 0 85. 6% 20. 0	85. 8% 19. 9 85. 8% 19. 9	86. 0% 19. 9 86. 0% 19. 9	86. 2% 19. 8 86. 2% 19. 8
			HK6025TE HK6025TF	150, 000	174		88.0%	A重油	16.5~19.8 16.5~19.8		84. 5% 20. 2 84. 5% 20. 2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85.6% 20.0	85. 8% 19. 9 85. 8% 19. 9	86.0% 19.9	86. 2% 19. 8
			HK6025TCS	150, 000	174		88.0%	A重油		静音形	84. 5% 20. 2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85.6% 20.0	85.8% 19.9	86.0% 19.9	86. 2% 19. 8
			HK6025TES	150, 000	174		88.0%		16.5~19.8	静音形	84. 5% 20. 2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85. 6% 20. 0	85. 8% 19. 9	86.0% 19.9	86. 2% 19. 8
			HK6025TFS	150, 000	174		88.0%		16.5~19.8	静音形	84.5% 20.2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85. 6% 20. 0	85.8% 19.9	86.0% 19.9	86. 2% 19. 8
			HK6025TCE	150, 000	174		88.0%	A重油	16.5~19.8		84. 5% 20. 2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85. 6% 20. 0	85.8% 19.9	86.0% 19.9	86. 2% 19. 8
			HK6025TEE	150, 000	174		88.0%		16.5~19.8		84.5% 20.2	84. 7% 20. 2		85. 2% 20. 1	85. 4% 20. 0	85. 6% 20. 0	85.8% 19.9	86.0% 19.9	86. 2% 19. 8
			HK6025TFE	150,000	174				16.5~19.8		84. 5% 20. 2	84. 7% 20. 2	84. 9% 20. 1	85. 2% 20. 1	85. 4% 20. 0	85. 6% 20. 0	85. 8% 19. 9	86.0% 19.9	86. 2% 19. 8
				現行機種(材料を					た場合の		6. 1%	5.9%	5. 6%	5.4%	5. 1%	4. 9%	4. 7%	4. 4%	4. 2%
				経年変化分 燃料消費節減率 ※同等熱出力換算										1	1				