

2021 年度      ネポンハウスカオンキ   熱効率および燃料消費量 経年変化一覧表

【目次】

・ HK-0型, 1型, 3型	1 へ -ジ
・ HK-4型, 5型, 6型	2 へ -ジ
・ HK-8型, 10型	3 へ -ジ
・ HK-11型, 15型, 20型	4 へ -ジ
・ HK-17型, 22型	5 へ -ジ
<hr/>	
・ HK-23型	6 へ -ジ
・ HK-25型, 25E型	7 へ -ジ
・ HK-25Z型	8 へ -ジ
・ HK-26型, 26Z型, 26V型 (現行)	9 へ -ジ
・ HK-24型	10 へ -ジ
<hr/>	
・ HK-24Z型	11 へ -ジ
・ HK-24V型 (現行)	12 へ -ジ
・ HK-27型	13 へ -ジ
・ HK-27Z型	14 へ -ジ
・ HK-27V型 (現行)	15 へ -ジ

2021年7月  
ネポン株式会社

ネブソン株式会社

【バスカオンキ 0.1, 3型シリーズ】 1/2 2021年度 熱効率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)					1965		1966		1967		1968		1969		1970		1971						
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
0型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	68.8%	5.3	69.0%	5.3					
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	68.8%	5.3	69.0%	5.3					
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	68.8%	14.4	69.0%	14.4					
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	68.8%	14.4	69.0%	14.4					
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9														69.0%	12.4				
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9															69.0%	12.4			
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2																69.0%	14.4		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2																	69.0%	14.4	
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5																		69.0%	20.6
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8																			69.0%
現行機種（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算									24.8%	24.5%	24.3%	24.0%	23.8%	23.5%	23.3%													

【バスカオンキ 0.1, 3型シリーズ】 2/2

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)					1972		1973		1974		1975		1976		1977		1978			
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
0型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.3%	5.3	69.5%	5.3	69.7%	5.2	69.9%	5.2	70.1%	5.2						
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.3%	5.3	69.5%	5.3	69.7%	5.2	69.9%	5.2	70.1%	5.2						
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1						
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1						
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5	69.3%	20.6	69.5%	20.5	69.7%	20.4	69.9%	20.4	70.1%	20.3	70.4%	20.3	70.6%	20.2		
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8	69.3%	24.7	69.5%	24.6	69.7%	24.5	69.9%	24.5	70.1%	24.4	70.4%	24.3	70.6%	24.2		
3型	1974 (S49)	1978 (S53)	HK303TE	75,000	87.2	10.7	80%	A重油	6.6~9.9					69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK303TC	75,000	87.2	10.7	80%	A重油	6.6~9.9					69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK403TE	87,000	101	12.3	80%	A重油	9.9~13.2					69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK403TC	87,000	101	12.3	80%	A重油	9.9~13.2					69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									23.0%	22.8%	22.6%	22.3%	22.1%	21.8%	21.6%										

ネポン株式会社

【ハウスオンキ 4, 5, 6型シリーズ】

2021 年度 熱効率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量														
				(kcal/h)	(kW)						1978		1979		1980		1981		1982		1983				
						%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)						
4 型 ・ 5 型	1978 (S53)	1981 (S56)	HK155SE	32,000	37.2	4.3	88.0%	A重油	3.3~4.95			78.6%	4.6	78.8%	4.6	79.0%	4.6	79.2%	4.6						
			HK155TE	32,000	37.2	4.3	88.0%	A重油	3.3~4.95				78.6%	4.6	78.8%	4.6	79.0%	4.6	79.2%	4.6					
			HK204TC	50,000	58.1	6.7	88.0%	A重油	4.95~6.6	低床タイプ			78.6%	7.3	78.8%	7.2	79.0%	7.2	79.2%	7.2					
			HK205TE	50,000	58.1	6.7	88.0%	A重油	4.95~6.6				78.6%	7.3	78.8%	7.2	79.0%	7.2	79.2%	7.2					
			HK205TC	50,000	58.1	6.7	88.0%	A重油	4.95~6.6				78.6%	7.3	78.8%	7.2	79.0%	7.2	79.2%	7.2					
			HK304TC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9	低床タイプ			78.6%	10.9	78.8%	10.9	79.0%	10.8	79.2%	10.8					
			HK305SE	75,000	87.2	10.0	88.0%	A重油	6.6~9.9				78.6%	10.9	78.8%	10.9	79.0%	10.8	79.2%	10.8					
			HK305SC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9				78.6%	10.9	78.8%	10.9	79.0%	10.8	79.2%	10.8					
			HK305TE	75,000	87.2	10.0	88.0%	A重油	6.6~9.9				78.6%	10.9	78.8%	10.9	79.0%	10.8	79.2%	10.8					
			HK305TC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9				78.6%	10.9	78.8%	10.9	79.0%	10.8	79.2%	10.8					
			HK404TC	87,000	101	11.6	88.0%	A重油	9.9~13.2	低床タイプ			78.6%	12.6	78.8%	12.6	79.0%	12.6	79.2%	12.5					
			HK405TE	87,000	101	11.6	88.0%	A重油	9.9~13.2				78.6%	12.6	78.8%	12.6	79.0%	12.6	79.2%	12.5					
			HK405TC	87,000	101	11.6	88.0%	A重油	9.9~13.2				78.6%	12.6	78.8%	12.6	79.0%	12.6	79.2%	12.5					
HK505TC	125,000	145	16.6	88.0%	A重油	13.2~16.5				78.6%	18.1	78.8%	18.1	79.0%	18.0	79.2%	18.0								
HK605TC	150,000	174	19.9	88.0%	A重油	16.5~19.8				78.6%	21.8	78.8%	21.7	79.0%	21.6	79.2%	21.6								
6 型	1981 (S56)	1983 (S58)	HK156SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95								79.2%	4.6	79.5%	4.6	79.7%	4.6			
			HK156TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95								79.2%	4.6	79.5%	4.6	79.7%	4.6			
			HK206TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								79.2%	7.2	79.5%	7.2	79.7%	7.2			
			HK206TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								79.2%	7.2	79.5%	7.2	79.7%	7.2			
			HK306SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								79.2%	10.8	79.5%	10.8	79.7%	10.7			
			HK306SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								79.2%	10.8	79.5%	10.8	79.7%	10.7			
			HK306TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								79.2%	10.8	79.5%	10.8	79.7%	10.7			
			HK306TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								79.2%	10.8	79.5%	10.8	79.7%	10.7			
			HK316TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	低床タイプ							79.2%	10.8	79.5%	10.8	79.7%	10.7			
			HK406TE	87,000	101	11.3	88.0%	A重油	9.9~13.2								79.2%	12.5	79.5%	12.5	79.7%	12.4			
			HK406TC	87,000	101	11.3	88.0%	A重油	9.9~13.2								79.2%	12.5	79.5%	12.5	79.7%	12.4			
			HK416TC	87,000	101	11.3	88.0%	A重油	9.9~13.2	低床タイプ							79.2%	12.5	79.5%	12.5	79.7%	12.4			
			HK506TC	125,000	145	16.2	88.0%	A重油	13.2~16.5								79.2%	18.0	79.5%	17.9	79.7%	17.9			
HK606TC	150,000	174	19.4	88.0%	A重油	16.5~19.8								79.2%	21.6	79.5%	21.5	79.7%	21.5						
現行機種（機器熱効率 90% ）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											12.7%	12.5%	12.2%	12.0%	11.7%	11.5%									

ネボン株式会社

【ハウスオキ 8, 10型シリーズ】

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988							
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)						
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			79.7%	4.6	79.9%	4.6	80.1%	4.6											
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95				79.7%	4.6	79.9%	4.6	80.1%	4.6										
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				79.7%	7.2	79.9%	7.1	80.1%	7.1										
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				79.7%	7.2	79.9%	7.1	80.1%	7.1										
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				79.7%	17.9	79.9%	17.8	80.1%	17.8										
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				79.7%	21.5	79.9%	21.4	80.1%	21.3										
10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95						80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5						
			HK160SC	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5					
			HK160TC	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5					
			HK160TEP	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			静音形					80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5				
			HK160TCP	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			静音形					80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5				
			HK210SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TEP	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			静音形					80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TCP	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			静音形					80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK310SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TEP	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			静音形					80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TCP	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			静音形					80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TCM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				システムバーナ				80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TEM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				システムバーナ				80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TFM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				システムバーナ				80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK410TE	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TC	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TF	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TEP	87,000	101	11.3	88.0%	A重油	9.9~13.2			静音形					80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TCP	87,000	101	11.3	88.0%	A重油	9.9~13.2			静音形					80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TCM	87,000	101	11.3	88.0%	A重油	9.9~13.2				システムバーナ				80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TEM	87,000	101	11.3	88.0%	A重油	9.9~13.2				システムバーナ				80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TFM	87,000	101	11.3	88.0%	A重油	9.9~13.2				システムバーナ				80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK510TC	125,000	145	16.2	88.0%	A重油	13.2~16.5								80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK510TCP	125,000	145	16.2	88.0%	A重油	13.2~16.5			静音形					80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5				システムバーナ				80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8								80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2				
			HK610TCP	150,000	174	19.4	88.0%	A重油	16.5~19.8			静音形					80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2				
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8				システムバーナ				80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2							
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4								80.1%	28.5	80.3%	28.4	80.5%	28.3	80.8%	28.2							
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											11.5%		11.2%		11.0%		10.7%		10.5%		10.3%							

ネポン株式会社

【ハウスカンキ 11, 15, 20型シリーズ】

2021年度 熱効率率/燃料消費量/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)						1987		1988		1989		1990		1991		1992		1993		1994		1995		
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
11型・ 15型・ 20型	1987 (S62)	1995 (H7)	HK1520SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1520SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1520TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1520TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1520TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1
			HK1520TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形		82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2	84.1%	5.2	84.3%	5.1
			HK2020SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2020SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2020TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2020TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2020TCP	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK2020TEP	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK2020TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK2020TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK3015TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3015TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3020TCP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TEP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TFP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TCD	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TED	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3020TFD	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3011TCE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK4015TC	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8	
			HK4015TF	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8	
			HK4020TC	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8	
			HK4020TE	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8	
			HK4020TF	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8	
			HK4020TCP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8
			HK4020TEP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8
			HK4020TFP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8
			HK4020TCS	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8
HK4020TES	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8			
HK4020TFS	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8			
HK4020TCD	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8			
HK4020TED	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8			
HK4020TFD	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8			
HK4011TCE	87,000	101	11.0	90.0%	A重油	9.9~13.2		82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8	84.1%	11.8	84.3%	11.8				
HK5015TC	125,000	145	15.8	90.0%	A重油	13.2~16.5		82.5%	17.3	82.8%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9				
HK5020TC	125,000	145	15.8	90.0%	A重油	13.2~16.5		82.5%	17.3	82.8%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9				
HK5020TCP	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形		82.5%	17.3	82.8%	17.2	83.0%	17.2	8														

ネポン株式会社

【ハウスコンキ 17, 22型シリーズ】

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						1995		1996		1997			
											%	(l/h)	%	(l/h)	%	(l/h)		
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			84.3%	5.1	84.5%	5.1	84.7%	5.1	
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			84.3%	5.1	84.5%	5.1	84.7%	5.1	
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			84.3%	5.1	84.5%	5.1	84.7%	5.1	
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			84.3%	5.1	84.5%	5.1	84.7%	5.1	
			HK1522TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		静音形		84.3%	5.1	84.5%	5.1	84.7%	5.1
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		静音形		84.3%	5.1	84.5%	5.1	84.7%	5.1
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		静音形		84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		静音形		84.3%	6.8	84.5%	6.7	84.7%	6.7
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		静音形		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		静音形		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		静音形		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9~13.2		静音形		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9~13.2		静音形		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9~13.2		静音形		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.3%	16.9	84.5%	16.9	84.7%	16.8
HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2~16.5		静音形		84.3%	16.9	84.5%	16.9	84.7%	16.8			
HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2~16.5		静音形		84.3%	16.9	84.5%	16.9	84.7%	16.8			
HK5017TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.3%	16.9	84.5%	16.9	84.7%	16.8			
HK6022TC	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6022TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5~19.8		静音形		84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5~19.8		静音形		84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6017TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK8022TF	200,000	233	19.0	90.0%	A重油	19.8~26.4				84.3%	27.0	84.5%	27.0	84.7%	26.9			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											6.3%		6.1%		5.8%			



ネポン株式会社

【ハウスファンキ 23型シリーズ】

2021 年度 熱効率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形			83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形			83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2~16.5				83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
HK5023TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9			
HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9			
HK6023TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6023TE	150,000	174	19.4	88.0%	A重油	16.5~19.8				83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6023TF	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6023TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											7.3%	7.1%	6.8%	6.6%	6.4%	6.1%								

ネポン株式会社

【ハウスコンド 25、25E型シリーズ】

2021年度 熱効率率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率率および燃料消費量																		
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005		
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
25型・ 25E型	1997 (H9)	2005 (H17)	HK1525SC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1	
			HK1525SE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1	
			HK1525TC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1	
			HK1525TE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1	
			HK1525TOP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1525TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形		82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK2025SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7	
			HK2025SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7	
			HK2025SR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7	
			HK2025TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7	
			HK2025TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7	
			HK2025TR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	スイング形		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2025TCS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2025TES	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2025TRS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形		82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK3025SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025SR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3025TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3025TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3025TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3025TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3025TCE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025TEE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK3025TFE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	
			HK4025TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK4025TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK4025TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK4025TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 50Hz		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 60Hz		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4025TCE	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK4025TEE	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK4025TFE	100,000	116	13.0	88.0%	A重油	9.9~13.2		82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	
			HK5025TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9	
			HK5025TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9	
			HK5025TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9	
			HK5025TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5025TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5025TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5025TCE	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9	
			HK5025TEE	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9	84.5%	16.9	
HK5025TFE	125,000	145	16.2	88.0%	A重油	13.2~16.5		82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	1												



ネボン株式会社  
【ハウスカンキ 25Z型シリーズ】

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																			
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9		
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9		
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2	
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2	
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2	
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5	
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5	
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5	
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8	
HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8				
HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8				
HK6025TRSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8			
HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8			
HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8			
HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	86.3%	19.8	86.5%	19.8			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											5.8%	5.6%	5.4%	5.1%	4.9%	4.6%	4.4%	4.1%	3.9%											

## ネボン株式会社

## 【ハスカネ 26型シリーズ】

## 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005		2006		2007	
				%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
26型	2000 (H12)	2007 (H19)	HK7026TC	172,000	200.0	22.3	88.0%	A重油	19.8~23.1		83.4%	23.5	83.6%	23.4	83.8%	23.4	84.1%	23.3	84.3%	23.3	84.5%	23.2	84.7%	23.1	84.9%	23.1
			HK7026TF	172,000	200.0	22.3	88.0%	A重油	19.8~23.1		83.4%	23.5	83.6%	23.4	83.8%	23.4	84.1%	23.3	84.3%	23.3	84.5%	23.2	84.7%	23.1	84.9%	23.1
			HK8026TC	197,800	230.0	25.6	88.0%	A重油	23.1~26.4		83.4%	27.0	83.6%	27.0	83.8%	26.9	84.1%	26.8	84.3%	26.8	84.5%	26.7	84.7%	26.6	84.9%	26.5
			HK8026TF	197,800	230.0	25.6	88.0%	A重油	23.1~26.4		83.4%	27.0	83.6%	27.0	83.8%	26.9	84.1%	26.8	84.3%	26.8	84.5%	26.7	84.7%	26.6	84.9%	26.5
現行機種（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算											7.3%	7.1%	6.8%	6.6%	6.4%	6.1%	5.9%	5.6%								

## 【ハスカネ 26Z型シリーズ】

## 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005		2006		2007	
				%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
26Z型	2000 (H12)	2007 (H19)	HK7026TCZ	172,000	200.0	21.8	90.0%	A重油	19.8~23.1		85.4%	23.0	85.6%	22.9	85.8%	22.8	86.1%	22.8	86.3%	22.7	86.5%	22.7	86.7%	22.6	86.9%	22.6
			HK7026TFZ	172,000	200.0	21.8	90.0%	A重油	19.8~23.1		85.4%	23.0	85.6%	22.9	85.8%	22.8	86.1%	22.8	86.3%	22.7	86.5%	22.7	86.7%	22.6	86.9%	22.6
			HK8026TCZ	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		85.4%	26.4	85.6%	26.3	85.8%	26.3	86.1%	26.2	86.3%	26.1	86.5%	26.1	86.7%	26.0	86.9%	25.9
			HK8026TFZ	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		85.4%	26.4	85.6%	26.3	85.8%	26.3	86.1%	26.2	86.3%	26.1	86.5%	26.1	86.7%	26.0	86.9%	25.9
現行機種（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算											5.1%	4.9%	4.6%	4.4%	4.1%	3.9%	3.7%	3.4%								

## 【ハスカネ 26V型シリーズ】 1/2

## 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2007		2008		2009		2010		2011		2012		2013		2014	
				%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
26V型	2007 (H19)	現行	HK8026TCV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6	88.2%	25.6	88.5%	25.5
			HK8026TCSV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4	静音形	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6	88.2%	25.6	88.5%	25.5
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6	88.2%	25.6	88.5%	25.5
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4	静音形	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6	88.2%	25.6	88.5%	25.5
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.4%	3.2%	2.9%	2.7%	2.4%	2.2%	1.9%	1.7%								

## 【ハスカネ 26V型シリーズ】 2/2

## 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量											
				(kcal/h)	(kW)						2015		2016		2017		2018		2019		2020	
				%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)			
26V型	2007 (H19)	現行	HK8026TCV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TCSV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4	静音形	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4		88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1~26.4	静音形	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											1.5%	1.2%	1.0%	0.7%	0.5%	0.2%						

ネボン株式会社

【ハウスカンキ 24型シリーズ】

2021 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量						
				(kcal/h)	(kW)						2005		2006		2007		
											%	(l/h)	%	(l/h)	%	(l/h)	
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3024TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK4024TC	100,000	116	13.0	88.0%	A重油	9.9~13.2			84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TE	100,000	116	13.0	88.0%	A重油	9.9~13.2			84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TF	100,000	116	13.0	88.0%	A重油	9.9~13.2			84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 50Hz		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 60Hz		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4024TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK5024TC	125,000	145	16.2	88.0%	A重油	13.2~16.5			84.5%	16.9	84.7%	16.8	84.9%	16.8
			HK5024TE	125,000	145	16.2	88.0%	A重油	13.2~16.5			84.5%	16.9	84.7%	16.8	84.9%	16.8
			HK5024TF	125,000	145	16.2	88.0%	A重油	13.2~16.5			84.5%	16.9	84.7%	16.8	84.9%	16.8
			HK5024TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		84.5%	16.9	84.7%	16.8	84.9%	16.8
HK5024TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5024TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形		84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK6024TC	150,000	174	19.4	88.0%	A重油	16.5~19.8			84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6024TE	150,000	174	19.4	88.0%	A重油	16.5~19.8			84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6024TF	150,000	174	19.4	88.0%	A重油	16.5~19.8			84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6024TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6024TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6024TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形		84.5%	20.2	84.7%	20.2	84.9%	20.1			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											6.1%		5.9%		5.6%		

ネボン 株式会社

【ハウスオンキ 24Z型シリーズ】

2021 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
											2005		2006		2007	
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)
24Z型	2005 (H17)	2007 (H19)	HK3024TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3024TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK4024TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TR5Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4024TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK5024TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5024TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5024TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5024TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4
HK5024TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4			
HK5024TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4			
HK6024TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6024TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6024TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6024TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6024TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6024TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										3.9%		3.7%		3.4%		

ネポン株式会社

【ハウスコンキ 24V型シリーズ】1/2 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)					2007		2008		2009		2010		2011		2012		2013	
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
24V型	2007 (H19)	現行	HK3024TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK3024TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK4024TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4024TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK5024TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
			HK5024TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
			HK5024TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
			HK6024TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4
			HK6024TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									3.4%		3.2%		2.9%		2.7%		2.4%		2.2%		1.9%		

【ハウスコンキ 24V型シリーズ】2/2 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)					2014		2015		2016		2017		2018		2019		2020	
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
24V型	2007 (H19)	現行	HK3024TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK3024TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK4024TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2	88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4024TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2	88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK5024TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5	88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
			HK5024TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5	88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
			HK5024TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5	88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
			HK6024TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8	88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4
			HK6024TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8	88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4
HK6024TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8	88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									1.7%		1.5%		1.2%		1.0%		0.7%		0.5%		0.2%		

ネボン株式会社  
【ハウスコンキ 27型シリーズ】

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
27型	2005 (H17)	2007 (H19)	HK1527SC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK1527SE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK1527TC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK1527TE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK1527TCP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形	84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK1527TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形	84.5%	5.1	84.7%	5.1	84.9%	5.1
			HK2027SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027SR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	スイング形	84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TCS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TES	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK2027TRS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.5%	6.7	84.7%	6.7	84.9%	6.7
			HK3027SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027SR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK3027TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.5%	10.1	84.7%	10.1	84.9%	10.1
			HK4027TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 50Hz	84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 60Hz	84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.5%	13.5	84.7%	13.5	84.9%	13.4
			HK4027TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.5%	13.5	84.7%	13.5	84.9%	13.4
HK4027TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.5%	13.5	84.7%	13.5	84.9%	13.4			
HK4027TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.5%	13.5	84.7%	13.5	84.9%	13.4			
HK5027TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5027TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5027TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5027TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5027TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK5027TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.5%	16.9	84.7%	16.8	84.9%	16.8			
HK6027TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6027TE	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6027TF	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6027TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6027TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.5%	20.2	84.7%	20.2	84.9%	20.1			
HK6027TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.5%	20.2	84.7%	20.2	84.9%	20.1			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											6.1%	5.9%	5.6%			



ネポン株式会社  
【ハウスホンキ 27Z型シリーズ】

## 2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
						%	(l/h)	%	(l/h)	%	(l/h)					
27Z型	2005 (H17)	2007 (H19)	HK1527TCZ	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1527TEZ	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK2027TCZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2027TEZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2027TRZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	スイング形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2027TCSZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2027TESZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2027TRSZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK3027TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3027TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK4027TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4027TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK5027TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5027TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5027TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5027TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5027TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5027TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4
HK6027TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6027TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6027TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6027TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6027TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6027TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										3.9%		3.7%		3.4%		

ネボン株式会社

【ハウスコンキ 27V型シリーズ】1/2

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2007		2008		2009		2010		2011		2012		2013			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
27V型	2007 (H19)	現行	HK1527TCV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			86.9%	5.0	87.2%	5.0	87.4%	5.0	87.6%	4.9	87.8%	4.9	88.0%	4.9	88.2%	4.9	
			HK1527TEV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				86.9%	5.0	87.2%	5.0	87.4%	5.0	87.6%	4.9	87.8%	4.9	88.0%	4.9	88.2%	4.9
			HK2027TCV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5	88.2%	6.5
			HK2027TEV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5	88.2%	6.5
			HK2027TRV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	スイング形			86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5	88.2%	6.5
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7
			HK4027TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4027TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4027TFV	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4027FRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4027GRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK4027TYV	100,000	116	12.7	90.0%	A重油	9.9~13.2	低床スイング形			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1
HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4			
HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4			
HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.4%		3.2%		2.9%		2.7%		2.4%		2.2%		1.9%			

【ハウスコンキ 27V型シリーズ】2/2

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2014		2015		2016		2017		2018		2019		2020			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
27V型	2007 (H19)	現行	HK1527TCV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			88.5%	5.0	88.7%	5.0	88.9%	5.0	89.1%	4.9	89.3%	4.9	89.6%	4.9	89.8%	4.9	
			HK1527TEV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				88.5%	5.0	88.7%	5.0	88.9%	5.0	89.1%	4.9	89.3%	4.9	89.6%	4.9	89.8%	4.9
			HK2027TCV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				88.5%	6.6	88.7%	6.5	88.9%	6.5	89.1%	6.5	89.3%	6.5	89.6%	6.5	89.8%	6.5
			HK2027TEV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				88.5%	6.6	88.7%	6.5	88.9%	6.5	89.1%	6.5	89.3%	6.5	89.6%	6.5	89.8%	6.5
			HK2027TRV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	スイング形			88.5%	6.6	88.7%	6.5	88.9%	6.5	89.1%	6.5	89.3%	6.5	89.6%	6.5	89.8%	6.5
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			88.5%	9.8	88.7%	9.8	88.9%	9.8	89.1%	9.8	89.3%	9.7	89.6%	9.7	89.8%	9.7
			HK4027TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2				88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4027TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2				88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4027TFV	100,000	116	12.7	90.0%	A重油	9.9~13.2				88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4027FRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz			88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4027GRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz			88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK4027TYV	100,000	116	12.7	90.0%	A重油	9.9~13.2	低床スイング形			88.5%	13.1	88.7%	13.1	88.9%	13.0	89.1%	13.0	89.3%	13.0	89.6%	13.0	89.8%	12.9
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5				88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5				88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5				88.5%	16.4	88.7%	16.4	88.9%	16.3	89.1%	16.3	89.3%	16.2	89.6%	16.2	89.8%	16.1
HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8				88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4			
HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8				88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4			
HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8				88.5%	19.7	88.7%	19.6	88.9%	19.6	89.1%	19.5	89.3%	19.5	89.6%	19.4	89.8%	19.4			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											1.7%		1.5%		1.2%		1.0%		0.7%		0.5%		0.2%			