

ネブソン株式会社

【バスカオンキ 0.1, 3型シリーズ】 1/2 2021年度 熱効率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				kcal/h)	(kW)					1965		1966		1967		1968		1969		1970		1971						
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
0型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	68.8%	5.3	69.0%	5.3					
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	68.8%	5.3	69.0%	5.3					
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	68.8%	12.4	69.0%	12.4					
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	68.8%	14.4	69.0%	14.4					
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	68.8%	14.4	69.0%	14.4					
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9														69.0%	12.4				
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9															69.0%	12.4			
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2																69.0%	14.4		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2																	69.0%	14.4	
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5																		69.0%	20.6
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8																			69.0%
現行機種（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算									24.8%	24.5%	24.3%	24.0%	23.8%	23.5%	23.3%													

【バスカオンキ 0.1, 3型シリーズ】 2/2

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量															
				kcal/h)	(kW)					1972		1973		1974		1975		1976		1977		1978			
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
0型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.3%	5.3	69.5%	5.3	69.7%	5.2	69.9%	5.2	70.1%	5.2						
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.3%	5.3	69.5%	5.3	69.7%	5.2	69.9%	5.2	70.1%	5.2						
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2						
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1						
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1						
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5	69.3%	20.6	69.5%	20.5	69.7%	20.4	69.9%	20.4	70.1%	20.3	70.4%	20.3	70.6%	20.2		
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8	69.3%	24.7	69.5%	24.6	69.7%	24.5	69.9%	24.5	70.1%	24.4	70.4%	24.3	70.6%	24.2		
3型	1974 (S49)	1978 (S53)	HK303TE	75,000	87.2	10.7	80%	A重油	6.6~9.9					69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK303TC	75,000	87.2	10.7	80%	A重油	6.6~9.9					69.7%	12.3	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1		
			HK403TE	87,000	101	12.3	80%	A重油	9.9~13.2					69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
			HK403TC	87,000	101	12.3	80%	A重油	9.9~13.2					69.7%	14.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1		
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									23.0%	22.8%	22.6%	22.3%	22.1%	21.8%	21.6%										