

ネボン株式会社

【ハウスオキ 8, 10型シリーズ】

2021年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988							
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)						
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			79.7%	4.6	79.9%	4.6	80.1%	4.6											
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95				79.7%	4.6	79.9%	4.6	80.1%	4.6										
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				79.7%	7.2	79.9%	7.1	80.1%	7.1										
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				79.7%	7.2	79.9%	7.1	80.1%	7.1										
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				79.7%	10.7	79.9%	10.7	80.1%	10.7										
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2				79.7%	12.4	79.9%	12.4	80.1%	12.4										
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				79.7%	17.9	79.9%	17.8	80.1%	17.8										
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				79.7%	21.5	79.9%	21.4	80.1%	21.3										
10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95						80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5						
			HK160SC	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5					
			HK160TC	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5					
			HK160TEP	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			静音形					80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5				
			HK160TCP	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			静音形					80.1%	4.6	80.3%	4.5	80.5%	4.5	80.8%	4.5				
			HK210SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6								80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TEP	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			静音形					80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK210TCP	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			静音形					80.1%	7.1	80.3%	7.1	80.5%	7.1	80.8%	7.1				
			HK310SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TEP	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			静音形					80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TCP	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			静音形					80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TCM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TEM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK310TFM	75,000	87.2	9.7	88.0%	A重油	6.6~9.9								80.1%	10.7	80.3%	10.6	80.5%	10.6	80.8%	10.6				
			HK410TE	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TC	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TF	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TEP	87,000	101	11.3	88.0%	A重油	9.9~13.2			静音形					80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TCP	87,000	101	11.3	88.0%	A重油	9.9~13.2			静音形					80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TCM	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TEM	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK410TFM	87,000	101	11.3	88.0%	A重油	9.9~13.2								80.1%	12.4	80.3%	12.3	80.5%	12.3	80.8%	12.3				
			HK510TC	125,000	145	16.2	88.0%	A重油	13.2~16.5								80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK510TCP	125,000	145	16.2	88.0%	A重油	13.2~16.5			静音形					80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5								80.1%	17.8	80.3%	17.7	80.5%	17.7	80.8%	17.6				
			HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8								80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2				
			HK610TCP	150,000	174	19.4	88.0%	A重油	16.5~19.8			静音形					80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2				
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8								80.1%	21.3	80.3%	21.3	80.5%	21.2	80.8%	21.2							
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4								80.1%	28.5	80.3%	28.4	80.5%	28.3	80.8%	28.2							
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											11.5%		11.2%		11.0%		10.7%		10.5%		10.3%							