

ネポン株式会社

【ハウスカオキ 17, 22型シリーズ】

2022 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						1995		1996		1997			
											%	(l/h)	%	(l/h)	%	(l/h)		
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			84.1%	5.2	84.3%	5.1	84.5%	5.1	
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1522TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			静音形	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			静音形	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0			静音形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0			静音形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9~13.2			静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9~13.2			静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9~13.2			静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.1%	16.9	84.3%	16.9	84.5%	16.9
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.1%	16.9	84.3%	16.9	84.5%	16.9
HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2~16.5			静音形	84.1%	16.9	84.3%	16.9	84.5%	16.9			
HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2~16.5			静音形	84.1%	16.9	84.3%	16.9	84.5%	16.9			
HK5017TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				84.1%	16.9	84.3%	16.9	84.5%	16.9			
HK6022TC	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6022TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5~19.8			静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5~19.8			静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK6017TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				84.1%	20.3	84.3%	20.3	84.5%	20.2			
HK8022TF	200,000	233	19.0	90.0%	A重油	19.8~26.4				84.1%	27.1	84.3%	27.0	84.5%	27.0			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											6.6%		6.3%		6.1%			