

ネポン株式会社

【ハウスオンキ 23型シリーズ】

2022年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1	
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形			83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	84.3%	10.1
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形			83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2				83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	84.3%	13.5
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2~16.5				83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2~16.5				83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK5023TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0	84.3%	16.9
			HK6023TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3
			HK6023TE	150,000	174	19.4	88.0%	A重油	16.5~19.8				83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3
HK6023TF	150,000	174	19.4	88.0%	A重油	16.5~19.8				83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3			
HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3			
HK6023TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3			
HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3	84.3%	20.3			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											7.6%		7.3%		7.1%		6.8%		6.6%		6.4%			