

ネポン株式会社
【ハウスファンキ 24型シリーズ】

2022 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK3024TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1
			HK4024TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形 50Hz	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形 60Hz	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK4024TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5
			HK5024TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5024TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5024TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5024TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5024TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK5024TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8
			HK6024TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2
			HK6024TE	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2
HK6024TF	150,000	174	19.4	88.0%	A重油	16.5~19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6024TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6024TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2			
HK6024TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										6.4%		6.1%		5.9%		