

ネポン 株式会社

【ハウスファンキ 24Z型シリーズ】

2022 年度 熱効率/燃料消費量 経年変化一覧表

| 製品 シリーズ | 製造 開始年 | 製造 終了年 | 製品型式 | 熱出力 | | 燃料 消費量 (l/h) | 熱効率 | 燃料 | 標準暖房 面積 (a) | 備考 | 製造年度別 経年変化による現在の熱効率および燃料消費量 | | | | | |
|---|---------------|---------------|------------|----------|------|--------------------|-------|-------|----------------|-------------|-----------------------------|-------|-------|-------|-------|-------|
| | | | | (kcal/h) | (kW) | | | | | | 2005 | | 2006 | | 2007 | |
| | | | | | | | | | | | % | (l/h) | % | (l/h) | % | (l/h) |
| 24Z型 | 2005 (H17) | 2007 (H19) | HK3024TCZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TEZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TFZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TRZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | スイング形 | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TCSZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | 静音形 | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TESZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | 静音形 | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK3024TFSZ | 75,000 | 87.2 | 9.5 | 90.0% | A重油 | 6.6~9.9 | 静音形 | 86.3% | 9.9 | 86.5% | 9.9 | 86.7% | 9.9 |
| | | | HK4024TCZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TEZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TFZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TR5Z | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | スイング形, 50Hz | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TR6Z | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | スイング形, 60Hz | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TCSZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | 静音形 | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TESZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | 静音形 | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TFSZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | 静音形 | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK4024TRSZ | 100,000 | 116 | 12.7 | 90.0% | A重油 | 9.9~13.2 | 静音形 | 86.3% | 13.2 | 86.5% | 13.2 | 86.7% | 13.1 |
| | | | HK5024TCZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 |
| | | | HK5024TEZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 |
| | | | HK5024TFZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 |
| | | | HK5024TCSZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | 静音形 | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 |
| HK5024TESZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | 静音形 | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 | | | |
| HK5024TFSZ | 125,000 | 145 | 15.8 | 90.0% | A重油 | 13.2~16.5 | 静音形 | 86.3% | 16.5 | 86.5% | 16.5 | 86.7% | 16.4 | | | |
| HK6024TCZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| HK6024TEZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| HK6024TFZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| HK6024TCSZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | 静音形 | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| HK6024TESZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | 静音形 | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| HK6024TFSZ | 150,000 | 174 | 19.0 | 90.0% | A重油 | 16.5~19.8 | 静音形 | 86.3% | 19.8 | 86.5% | 19.8 | 86.7% | 19.7 | | | |
| 現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算 | | | | | | | | | | 4.1% | | 3.9% | | 3.7% | | |