

2023 年度 ネポンハウスカオンキ 熱効率および燃料消費量 経年変化一覧表

【目次】

・ HK-0 型, 1 型, 3 型	1 ページ
・ HK-4 型, 5 型, 6 型	2 ページ
・ HK-8 型, 10 型	3 ページ
・ HK-11 型, 15 型, 20 型	4 ページ
・ HK-17 型, 22 型	5 ページ
・ HK-23 型	6 ページ
・ HK-25 型, 25E 型	7 ページ
・ HK-25Z 型	8 ページ
・ HK-26 型, 26Z 型, 26V 型	9 ページ
・ HK-24 型	10 ページ
・ HK-24Z 型	11 ページ
・ HK-24V 型	12 ページ
・ HK-27 型	13 ページ
・ HK-27Z 型	14 ページ
・ HK-27V 型	15 ページ

2023年7月
ネポン株式会社

ネポン株式会社

【ハウスオキ 0.1, 3型シリーズ】 1/2

2023 年度

熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量														
				(kcal/h)	(kW)					1965		1966		1967		1968		1969		1970		1971		
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
O 型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A 重油	2.3～5.0	67.3%	5.4	67.5%	5.4	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	
			HK150SE	32,000	37.2	4.6	80%	A 重油	2.3～5.0	67.3%	5.4	67.5%	5.4	67.7%	5.4	67.9%	5.4	68.2%	5.4	68.4%	5.3	68.6%	5.3	
			HK300TE	75,000	87.2	10.7	80%	A 重油	6.6～9.9	67.3%	12.7	67.5%	12.7	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	
			HK300TC	75,000	87.2	10.7	80%	A 重油	6.6～9.9	67.3%	12.7	67.5%	12.7	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	
			HK300SE	75,000	87.2	10.7	80%	A 重油	6.6～9.9	67.3%	12.7	67.5%	12.7	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	
			HK300SC	75,000	87.2	10.7	80%	A 重油	6.6～9.9	67.3%	12.7	67.5%	12.7	67.7%	12.6	67.9%	12.6	68.2%	12.5	68.4%	12.5	68.6%	12.5	
			HK400TE	87,000	101	12.3	80%	A 重油	9.9～13.2	67.3%	14.7	67.5%	14.7	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	
			HK400TC	87,000	101	12.3	80%	A 重油	9.9～13.2	67.3%	14.7	67.5%	14.7	67.7%	14.6	67.9%	14.6	68.2%	14.6	68.4%	14.5	68.6%	14.5	
			HK500TC	125,000	145	17.8	80%	A 重油	13.2～16.5	67.3%	21.2	67.5%	21.1	67.7%	21.0	67.9%	21.0	68.2%	20.9	68.4%	20.8	68.6%	20.8	
HK600TC	150,000	174	21.3	80%	A 重油	16.5～19.8	67.3%	25.4	67.5%	25.3	67.7%	25.2	67.9%	25.2	68.2%	25.1	68.4%	25.0	68.6%	24.9				
1 型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A 重油	6.6～9.9													68.6%	12.5	
			HK301TC	75,000	87.2	10.7	80%	A 重油	6.6～9.9														68.6%	12.5
			HK401TE	87,000	101	12.3	80%	A 重油	9.9～13.2														68.6%	14.5
			HK401TC	87,000	101	12.3	80%	A 重油	9.9～13.2														68.6%	14.5
			HK501TC	125,000	145	17.8	80%	A 重油	13.2～16.5														68.6%	20.8
			HK601TC	150,000	174	21.3	80%	A 重油	16.5～19.8														68.6%	24.9
			現行機種HK30型（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算									25.2%		25.0%		24.8%		24.5%		24.3%		24.0%		23.8%

【ハウスオキ 0.1, 3型シリーズ】 2/2

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)					1972		1973		1974		1975		1976		1977		1978	
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
0 型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A 重油	2.3～5.0	68.8%	5.3	69.0%	5.3	69.3%	5.3	69.5%	5.3	69.7%	5.2				
			HK150SE	32,000	37.2	4.6	80%	A 重油	2.3～5.0	68.8%	5.3	69.0%	5.3	69.3%	5.3	69.5%	5.3	69.7%	5.2				
			HK300TE	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3				
			HK300TC	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3				
			HK300SE	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3				
			HK300SC	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3				
			HK400TE	87,000	101	12.3	80%	A 重油	9.9～13.2	68.8%	14.4	69.0%	14.4	69.3%	14.3	69.5%	14.3	69.7%	14.2				
			HK400TC	87,000	101	12.3	80%	A 重油	9.9～13.2	68.8%	14.4	69.0%	14.4	69.3%	14.3	69.5%	14.3	69.7%	14.2				
			HK500TC	125,000	145	17.8	80%	A 重油	13.2～16.5	68.8%	20.7	69.0%	20.6	69.3%	20.6	69.5%	20.5	69.7%	20.4				
			HK600TC	150,000	174	21.3	80%	A 重油	16.5～19.8	68.8%	24.8	69.0%	24.8	69.3%	24.7	69.5%	24.6	69.7%	24.5				
1 型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2
			HK301TC	75,000	87.2	10.7	80%	A 重油	6.6～9.9	68.8%	12.4	69.0%	12.4	69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2
			HK401TE	87,000	101	12.3	80%	A 重油	9.9～13.2	68.8%	14.4	69.0%	14.4	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1
			HK401TC	87,000	101	12.3	80%	A 重油	9.9～13.2	68.8%	14.4	69.0%	14.4	69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1
			HK501TC	125,000	145	17.8	80%	A 重油	13.2～16.5	68.8%	20.7	69.0%	20.6	69.3%	20.6	69.5%	20.5	69.7%	20.4	69.9%	20.4	70.1%	20.3
			HK601TC	150,000	174	21.3	80%	A 重油	16.5～19.8	68.8%	24.8	69.0%	24.8	69.3%	24.7	69.5%	24.6	69.7%	24.5	69.9%	24.5	70.1%	24.4
3 型	1974 (S49)	1978 (S53)	HK303TE	75,000	87.2	10.7	80%	A 重油	6.6～9.9					69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2
			HK303TC	75,000	87.2	10.7	80%	A 重油	6.6～9.9					69.3%	12.3	69.5%	12.3	69.7%	12.3	69.9%	12.2	70.1%	12.2
			HK403TE	87,000	101	12.3	80%	A 重油	9.9～13.2					69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1
			HK403TC	87,000	101	12.3	80%	A 重油	9.9～13.2					69.3%	14.3	69.5%	14.3	69.7%	14.2	69.9%	14.2	70.1%	14.1
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算										23.5%		23.3%		23.0%		22.8%		22.6%		22.3%		22.1%	

ネポン株式会社

【ハウスオンキ 4, 5, 6型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量											
				(kcal/h)	(kW)						1978		1979		1980		1981		1982		1983	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
4 型 ・ 5 型	1978 (S53)	1981 (S56)	HK155SE	32,000	37.2	4.3	88.0%	A 重油	3.3～4.95		78.1%	4.7	78.4%	4.7	78.6%	4.6	78.8%	4.6				
			HK155TE	32,000	37.2	4.3	88.0%	A 重油	3.3～4.95		78.1%	4.7	78.4%	4.7	78.6%	4.6	78.8%	4.6				
			HK204TC	50,000	58.1	6.7	88.0%	A 重油	4.95～6.6	低床タイプ	78.1%	7.3	78.4%	7.3	78.6%	7.3	78.8%	7.2				
			HK205TE	50,000	58.1	6.7	88.0%	A 重油	4.95～6.6		78.1%	7.3	78.4%	7.3	78.6%	7.3	78.8%	7.2				
			HK205TC	50,000	58.1	6.7	88.0%	A 重油	4.95～6.6		78.1%	7.3	78.4%	7.3	78.6%	7.3	78.8%	7.2				
			HK304TC	75,000	87.2	10.0	88.0%	A 重油	6.6～9.9	低床タイプ	78.1%	10.9	78.4%	10.9	78.6%	10.9	78.8%	10.9				
			HK305SE	75,000	87.2	10.0	88.0%	A 重油	6.6～9.9		78.1%	10.9	78.4%	10.9	78.6%	10.9	78.8%	10.9				
			HK305SC	75,000	87.2	10.0	88.0%	A 重油	6.6～9.9		78.1%	10.9	78.4%	10.9	78.6%	10.9	78.8%	10.9				
			HK305TE	75,000	87.2	10.0	88.0%	A 重油	6.6～9.9		78.1%	10.9	78.4%	10.9	78.6%	10.9	78.8%	10.9				
			HK305TC	75,000	87.2	10.0	88.0%	A 重油	6.6～9.9		78.1%	10.9	78.4%	10.9	78.6%	10.9	78.8%	10.9				
			HK404TC	87,000	101	11.6	88.0%	A 重油	9.9～13.2	低床タイプ	78.1%	12.7	78.4%	12.7	78.6%	12.6	78.8%	12.6				
			HK405TE	87,000	101	11.6	88.0%	A 重油	9.9～13.2		78.1%	12.7	78.4%	12.7	78.6%	12.6	78.8%	12.6				
HK405TC	87,000	101	11.6	88.0%	A 重油	9.9～13.2		78.1%	12.7	78.4%	12.7	78.6%	12.6	78.8%	12.6							
HK505TC	125,000	145	16.6	88.0%	A 重油	13.2～16.5		78.1%	18.2	78.4%	18.2	78.6%	18.1	78.8%	18.1							
HK605TC	150,000	174	19.9	88.0%	A 重油	16.5～19.8		78.1%	21.9	78.4%	21.8	78.6%	21.8	78.8%	21.7							
6 型	1981 (S56)	1983 (S58)	HK156SE	32,000	37.2	4.2	88.0%	A 重油	3.3～4.95							78.8%	4.6	79.0%	4.6	79.2%	4.6	
			HK156TE	32,000	37.2	4.2	88.0%	A 重油	3.3～4.95							78.8%	4.6	79.0%	4.6	79.2%	4.6	
			HK206TE	50,000	58.1	6.5	88.0%	A 重油	4.95～6.6							78.8%	7.2	79.0%	7.2	79.2%	7.2	
			HK206TC	50,000	58.1	6.5	88.0%	A 重油	4.95～6.6							78.8%	7.2	79.0%	7.2	79.2%	7.2	
			HK306SE	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9							78.8%	10.9	79.0%	10.8	79.2%	10.8	
			HK306SC	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9							78.8%	10.9	79.0%	10.8	79.2%	10.8	
			HK306TE	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9							78.8%	10.9	79.0%	10.8	79.2%	10.8	
			HK306TC	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9							78.8%	10.9	79.0%	10.8	79.2%	10.8	
			HK316TC	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9	低床タイプ						78.8%	10.9	79.0%	10.8	79.2%	10.8	
			HK406TE	87,000	101	11.3	88.0%	A 重油	9.9～13.2							78.8%	12.6	79.0%	12.6	79.2%	12.5	
			HK406TC	87,000	101	11.3	88.0%	A 重油	9.9～13.2							78.8%	12.6	79.0%	12.6	79.2%	12.5	
			HK416TC	87,000	101	11.3	88.0%	A 重油	9.9～13.2	低床タイプ						78.8%	12.6	79.0%	12.6	79.2%	12.5	
			HK506TC	125,000	145	16.2	88.0%	A 重油	13.2～16.5							78.8%	18.1	79.0%	18.0	79.2%	18.0	
			HK606TC	150,000	174	19.4	88.0%	A 重油	16.5～19.8							78.8%	21.7	79.0%	21.6	79.2%	21.6	
現行機種HK30型（機器熱効率 90% ）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											13.2%		12.9%		12.7%		12.5%		12.2%		12.0%	

ネボン株式会社

【ハウスコナ 8.10型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
8 型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95			79.2%	4.6	79.5%	4.6	79.7%	4.6							
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95			79.2%	4.6	79.5%	4.6	79.7%	4.6							
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			79.2%	7.2	79.5%	7.2	79.7%	7.2							
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			79.2%	7.2	79.5%	7.2	79.7%	7.2							
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
10 型	1985 (S60)	1988 (S63)	HK408TC	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2～16.5			79.2%	18.0	79.5%	17.9	79.7%	17.9							
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5～19.8			79.2%	21.6	79.5%	21.5	79.7%	21.5							
			HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5	
			HK160SC	32,000	37.2	4.2	88.0%	A重油	3.3～4.95							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5	
			HK160TE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5	
			HK160TC	32,000	37.2	4.2	88.0%	A重油	3.3～4.95							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5	
			HK160TEP	32,000	37.2	4.2	88.0%	A重油	3.3～4.95	静音形							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5
			HK160TCP	32,000	37.2	4.2	88.0%	A重油	3.3～4.95	静音形							79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5
			HK210SE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1	
			HK210SC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1	
			HK210TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1	
			HK210TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1	
			HK210TEP	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1
			HK210TCP	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形							79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1
			HK310SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6	
			HK310SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6	
			HK310TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6	
			HK310TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6	
			HK310TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6	
			HK310TEP	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6
			HK310TCP	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6
			HK310TCM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6
			HK310TEM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6
			HK310TFM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー							79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6
			HK410TE	87,000	101	11.3	88.0%	A重油	9.9～13.2								79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TC	87,000	101	11.3	88.0%	A重油	9.9～13.2								79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TF	87,000	101	11.3	88.0%	A重油	9.9～13.2								79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TEP	87,000	101	11.3	88.0%	A重油	9.9～13.2	静音形							79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TCP	87,000	101	11.3	88.0%	A重油	9.9～13.2	静音形							79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TCM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー							79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TEM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー							79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK410TFM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー							79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3
			HK510TC	125,000	145	16.2	88.0%	A重油	13.2～16.5								79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7
			HK510TCP	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形							79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7
			HK510TCM	125,000	145	16.2	88.0%	A重油	13.2～16.5	システムバナー							79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7
			HK610TC	150,000	174	19.4	88.0%	A重油	16.5～19.8								79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3
			HK610TCP	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形							79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5～19.8	システムバナー							79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3			
HK810TC	200,000	233	25.9	88.0%	A重油	19.8～26.4								79.7%	28.6	79.9%	28.5	80.1%	28.5	80.3%	28.4			
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											12.0%		11.7%		11.5%		11.2%		11.0%		10.7%			

ネポン株式会社

【バスカン 11, 15, 20型シリーズ】

2023 年度 熱効率/燃料消費量 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1987		1988		1989		1990		1991		1992		1993		1994		1995	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
11型・ 15型・ 20型	1987 (S62)	1995 (H7)	HK1520SC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK1520SE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK1520TC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK1520TE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK1520TCP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK1520TEP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.9%	5.2
			HK2020SC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020SE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TCP	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TEP	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TCS	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK2020TES	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.9%	6.8
			HK3015TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3015TF	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020SC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020SE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TF	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TCP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TEP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TFP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TCS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TES	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TFS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TCD	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TFD	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3020TFD	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK3011TCE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.2	83.6%	10.2	83.9%	10.2
			HK4015TC	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4015TF	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TC	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TE	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TF	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TCP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TEP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TFP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TCS	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TES	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TFS	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
			HK4020TCD	87,000	101	11.0	90.0%	A重油	9.9～13.2	デラックス形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8
HK4020TED	87,000	101	11.0	90.0%	A重油	9.9～13.2	デラックス形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8			
HK4020TFD	87,000	101	11.0	90.0%	A重油	9.9～13.2	デラックス形	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8			
HK4011TCE	87,000	101	11.0	90.0%	A重油	9.9～13.2		82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9	83.4%	11.9	83.6%	11.9	83.9%	11.8			
HK5015TC	125,000	145</																										

ネポン株式会社

【ハウスカオキ 17, 22型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
											1995		1996		1997			
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)		
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95			83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95			83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95			83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95			83.9%	5.2	84.1%	5.2	84.3%	5.1	
			HK1522TOP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形			83.9%	5.2	84.1%	5.2	84.3%	5.1
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形			83.9%	5.2	84.1%	5.2	84.3%	5.1
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0			83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0			83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0			83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0			83.9%	6.8	84.1%	6.8	84.3%	6.8	
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形			83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形			83.9%	6.8	84.1%	6.8	84.3%	6.8
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			83.9%	10.2	84.1%	10.2	84.3%	10.1
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			83.9%	10.2	84.1%	10.2	84.3%	10.1	
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9～13.2			83.9%	13.6	84.1%	13.6	84.3%	13.5	
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9～13.2			83.9%	13.6	84.1%	13.6	84.3%	13.5	
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9～13.2			83.9%	13.6	84.1%	13.6	84.3%	13.5	
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			83.9%	13.6	84.1%	13.6	84.3%	13.5
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			83.9%	13.6	84.1%	13.6	84.3%	13.5
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			83.9%	13.6	84.1%	13.6	84.3%	13.5
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9～13.2			83.9%	13.6	84.1%	13.6	84.3%	13.5	
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9～13.2			83.9%	13.6	84.1%	13.6	84.3%	13.5	
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2～16.5			83.9%	17.0	84.1%	16.9	84.3%	16.9	
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2～16.5			83.9%	17.0	84.1%	16.9	84.3%	16.9	
			HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形			83.9%	17.0	84.1%	16.9	84.3%	16.9
			HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形			83.9%	17.0	84.1%	16.9	84.3%	16.9
			HK5017TF	125,000	145	15.8	90.0%	A重油	13.2～16.5			83.9%	17.0	84.1%	16.9	84.3%	16.9	
			HK6022TC	150,000	174	19.0	90.0%	A重油	16.5～19.8			83.9%	20.4	84.1%	20.3	84.3%	20.3	
			HK6022TF	150,000	174	19.0	90.0%	A重油	16.5～19.8			83.9%	20.4	84.1%	20.3	84.3%	20.3	
			HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形			83.9%	20.4	84.1%	20.3	84.3%	20.3
			HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形			83.9%	20.4	84.1%	20.3	84.3%	20.3
			HK6017TF	150,000	174	19.0	90.0%	A重油	16.5～19.8			83.9%	20.4	84.1%	20.3	84.3%	20.3	
			HK8022TF	200,000	233	19.0	90.0%	A重油	19.8～26.4			83.9%	27.2	84.1%	27.1	84.3%	27.0	
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											6.8%		6.6%		6.3%			

ネポン株式会社

【ハウスオンキ 23型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量												
											2000		2001		2002		2003		2004		2005		
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形		83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形		83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形		83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形		83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9～13.2			83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9～13.2			83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9～13.2			83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形		83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形		83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形		83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形		83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9～13.2			83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2～16.5			83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2～16.5			83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2～16.5			83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形		83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5023TES	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形		83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形		83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK6023TC	150,000	174	19.4	88.0%	A重油	16.5～19.8			83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
			HK6023TE	150,000	174	19.4	88.0%	A重油	16.5～19.8			83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
			HK6023TF	150,000	174	19.4	88.0%	A重油	16.5～19.8			83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
			HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形		83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
			HK6023TES	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形		83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
			HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形		83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4	84.1%	20.3
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											7.8%		7.6%		7.3%		7.1%		6.8%		6.6%		

ネパシ株式会社

【バスカネ 25、25E型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																			
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
25型 ・ 25E型	1997 (H9)	2005 (H17)	HK1525SC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	
			HK1525SE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	
			HK1525TC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	
			HK1525TE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2	
			HK1525TCP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525TEP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形			82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK2025SC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	
			HK2025SE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	
			HK2025SR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	
			HK2025TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	
			HK2025TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8	
			HK2025TR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	スイング形			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TCS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TES	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TRS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形			82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK3025SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025SR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025TR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TCS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TES	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TFS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TCE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025TEE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK3025TFE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2	
			HK4025TC	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK4025TE	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK4025TF	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK4025TR5	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 50Hz			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TR6	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 60Hz			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TCS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TES	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TFS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TRS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TCE	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK4025TEE	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK4025TFE	100,000	116	13.0	88.0%	A重油	9.9～13.2			82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6	
			HK5025TC	125,000	145	16.2	88.0%																							

ネポン株式会社

【ハウスカネ 25Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											6.3%		6.1%		5.8%		5.6%		5.4%		5.1%		4.9%		4.6%		4.4%	

ネポン株式会社

【ハウスファンキ 26型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
26型	2000 (H12)	2007 (H19)	HK7026TC	172,000	200.0	22.3	88.0%	A重油	19.8～23.1		83.0%	23.6	83.2%	23.6	83.4%	23.5	83.6%	23.4	83.8%	23.4	84.1%	23.3	84.3%	23.3	84.5%	23.2
			HK7026TF	172,000	200.0	22.3	88.0%	A重油	19.8～23.1		83.0%	23.6	83.2%	23.6	83.4%	23.5	83.6%	23.4	83.8%	23.4	84.1%	23.3	84.3%	23.3	84.5%	23.2
			HK8026TC	197,800	230.0	25.6	88.0%	A重油	23.1～26.4		83.0%	27.2	83.2%	27.1	83.4%	27.0	83.6%	27.0	83.8%	26.9	84.1%	26.8	84.3%	26.8	84.5%	26.7
			HK8026TF	197,800	230.0	25.6	88.0%	A重油	23.1～26.4		83.0%	27.2	83.2%	27.1	83.4%	27.0	83.6%	27.0	83.8%	26.9	84.1%	26.8	84.3%	26.8	84.5%	26.7
			現行機種HK30型（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算										7.8%		7.6%		7.3%		7.1%		6.8%		6.6%		6.4%	

【ハウスファンキ 26Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
26Z型	2000 (H12)	2007 (H19)	HK7026TCZ	172,000	200.0	21.8	90.0%	A重油	19.8～23.1		85.0%	23.1	85.2%	23.0	85.4%	23.0	85.6%	22.9	85.8%	22.8	86.1%	22.8	86.3%	22.7	86.5%	22.7
			HK7026TFZ	172,000	200.0	21.8	90.0%	A重油	19.8～23.1		85.0%	23.1	85.2%	23.0	85.4%	23.0	85.6%	22.9	85.8%	22.8	86.1%	22.8	86.3%	22.7	86.5%	22.7
			HK8026TCZ	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		85.0%	26.5	85.2%	26.5	85.4%	26.4	85.6%	26.3	85.8%	26.3	86.1%	26.2	86.3%	26.1	86.5%	26.1
			HK8026TFZ	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		85.0%	26.5	85.2%	26.5	85.4%	26.4	85.6%	26.3	85.8%	26.3	86.1%	26.2	86.3%	26.1	86.5%	26.1
			現行機種HK30型（機器熱効率 90%）へ更新した場合の 経年変化節減率 ※同等熱出力換算										5.6%		5.4%		5.1%		4.9%		4.6%		4.4%		4.1%	

【ハウスファンキ 26V型シリーズ】 1/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2007		2008		2009		2010		2011		2012		2013		2014	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
26V型	2007 (H19)	2023 (R5)	HK8026TCV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		86.5%	26.1	86.7%	26.0	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6
			HK8026TCSV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4	静音形	86.5%	26.1	86.7%	26.0	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		86.5%	26.1	86.7%	26.0	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6
			HK8026TFSV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4	静音形	86.5%	26.1	86.7%	26.0	86.9%	25.9	87.2%	25.9	87.4%	25.8	87.6%	25.7	87.8%	25.7	88.0%	25.6
			現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											3.9%		3.7%		3.4%		3.2%		2.9%		2.7%		2.4%

【ハウスファンキ 26V型シリーズ】 2/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2015		2016		2017		2018		2019		2020		2021		2022	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
26V型	2007 (H19)	2023 (R5)	HK8026TCV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		88.2%	25.6	88.5%	25.5	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TCSV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4	静音形	88.2%	25.6	88.5%	25.5	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TFV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4		88.2%	25.6	88.5%	25.5	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			HK8026TFSV	197,800	230.0	25.1	90.0%	A重油	23.1～26.4	静音形	88.2%	25.6	88.5%	25.5	88.7%	25.4	88.9%	25.4	89.1%	25.3	89.3%	25.2	89.6%	25.2	89.8%	25.1
			現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											1.9%		1.7%		1.5%		1.2%		1.0%		0.7%		0.5%

ネポン株式会社
【ハウスカンキ 24型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
											2005		2006		2007	
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TCS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TES	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3024TFS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK4024TC	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TE	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TF	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TR5	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 50Hz	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TR6	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 60Hz	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TCS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TES	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TFS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4024TRS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK5024TC	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5024TE	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5024TF	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5024TCS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5024TES	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5024TFS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK6024TC	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6024TE	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6024TF	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6024TCS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6024TES	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6024TFS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											6.6%		6.4%		6.1%	

ネポン 株式会社

【ハウスファンキ 24Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24Z型	2005 (H17)	2007 (H19)	HK3024TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK4024TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK5024TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK6024TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											4.4%		4.1%		3.9%	

ネボン株式会社

【ハウスカナンキ 24V型シリーズ】 1/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)					2007		2008		2009		2010		2011		2012		2013		2014	
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
24V型	2007 (H19)	2023 (R5)	HK3024TCV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK3024TEV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK4024TCV	100,000	116	12.6	90.0%	A重油	9.9～13.2	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4024TEV	100,000	116	12.6	90.0%	A重油	9.9～13.2	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK5024TCV	125,000	145	15.8	90.0%	A重油	13.2～16.5	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK5024TEV	125,000	145	15.8	90.0%	A重油	13.2～16.5	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK5024TFV	125,000	145	15.8	90.0%	A重油	13.2～16.5	86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK6024TCV	150,000	174	19.0	90.0%	A重油	16.5～19.8	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
			HK6024TEV	150,000	174	19.0	90.0%	A重油	16.5～19.8	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
			HK6024TFV	150,000	174	19.0	90.0%	A重油	16.5～19.8	86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算									3.9%		3.7%		3.4%		3.2%		2.9%		2.7%		2.4%		2.2%		

【ハウスカナンキ 24V型シリーズ】 2/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量																				
				(kcal/h)	(kW)					2015		2016		2017		2018		2019		2020		2021		2022						
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
24V型	2007 (H19)	2023 (R5)	HK3024TCV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK3024TEV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK4024TCV	100,000	116	12.6	90.0%	A重油	9.9～13.2	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4024TEV	100,000	116	12.6	90.0%	A重油	9.9～13.2	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK5024TCV	125,000	145	15.8	90.0%	A重油	13.2～16.5	88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK5024TEV	125,000	145	15.8	90.0%	A重油	13.2～16.5	88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK5024TFV	125,000	145	15.8	90.0%	A重油	13.2～16.5	88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK6024TCV	150,000	174	19.0	90.0%	A重油	16.5～19.8	88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
			HK6024TEV	150,000	174	19.0	90.0%	A重油	16.5～19.8	88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
			HK6024TFV	150,000	174	19.0	90.0%	A重油	16.5～19.8	88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
現行機種HK30型（機器熱効率 経年変化節減率 ※同等熱出力換算									90%	）へ設備更新した場合の																				
									1.9%			1.7%			1.5%			1.2%			1.0%			0.7%			0.5%			0.2%

ネ ボ ン 株式会社
【ハウスオンキ 27型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
27型	2005 (H17)	2007 (H19)	HK1527SC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1527SE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1527TC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1527TE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1527TCP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK1527TEP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形	84.1%	5.2	84.3%	5.1	84.5%	5.1
			HK2027SC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027SE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027SR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	スイング形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TCS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TES	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK2027TRS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	84.1%	6.8	84.3%	6.8	84.5%	6.7
			HK3027SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027SR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TCS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TES	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK3027TFS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	84.1%	10.2	84.3%	10.1	84.5%	10.1
			HK4027TC	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TE	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TF	100,000	116	13.0	88.0%	A重油	9.9～13.2		84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TR5	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 50Hz	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TR6	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 60Hz	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TCS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TES	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TFS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK4027TRS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	84.1%	13.6	84.3%	13.5	84.5%	13.5
			HK5027TC	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5027TE	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5027TF	125,000	145	16.2	88.0%	A重油	13.2～16.5		84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5027TCS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5027TES	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK5027TFS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	84.1%	17.0	84.3%	16.9	84.5%	16.9
			HK6027TC	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6027TE	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6027TF	150,000	174	19.4	88.0%	A重油	16.5～19.8		84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6027TCS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6027TES	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
			HK6027TFS	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形	84.1%	20.3	84.3%	20.3	84.5%	20.2
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											6.6%		6.4%		6.1%	

ネポソ株式会社

【ハウスファンキ 27Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
27Z型	2005 (H17)	2007 (H19)	HK1527TCZ	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK1527TEZ	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK2027TCZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6		86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TEZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6		86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TRZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	スイング形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TCSZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TESZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TRSZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK3027TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK4027TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK5027TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK6027TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											4.4%		4.1%		3.9%	

ネ ポ ン 株式会社

【ハウスオンキ 27V型シリーズ】 1/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																				
											2007		2008		2009		2010		2011		2012		2013		2014						
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
27V型	2007 (H19)	2023 (R5)	HK1527TCV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0															
			HK1527TEV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0															
			HK2027TCV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5					
			HK2027TEV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5					
			HK2027TRV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6	スイング形	86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5					
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7					
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7					
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7					
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7					
			HK4027TCV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK4027TEV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK4027TFV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK4027FRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スイング形, 50Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK4027GRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スイング形, 60Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK4027TYV	100,000	116	12.6	90.0%	A重油	9.9~13.2	低床スイング形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0					
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2					
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2					
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2					
			HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4					
			HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4					
			HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4					
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											3.9%		3.7%		3.4%		3.2%		2.9%		2.7%		2.4%		2.2%						

【ハウスオンキ 27V型シリーズ】 2/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																				
											2015		2016		2017		2018		2019		2020		2021		2022						
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
27V型	2007 (H19)	2023 (R5)	HK2027TCV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3					
			HK2027TEV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3					
			HK2027TRV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6	スイング形	88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3					
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5					
			HK4027TCV	100,000	116	12.6	90.0%	A重油	9.9~13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4027TEV	100,000	116	12.6	90.0%	A重油	9.9~13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4027TFV	100,000	116	12.6	90.0%	A重油	9.9~13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4027FRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スイング形, 50Hz	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4027GRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スイング形, 60Hz	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK4027TYV	100,000	116	12.6	90.0%	A重油	9.9~13.2	低床スイング形	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7					
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9					
			HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
			HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
			HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0					
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											1.9%		1.7%		1.5%		1.2%		1.0%		0.7%		0.5%		0.2%						