

ネボン株式会社

【ハウスカナンキ 24V型シリーズ】 1/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

| 製品<br>シリーズ                                         | 製造<br>開始年     | 製造<br>終了年    | 製品型式      | 熱出力      |      | 燃料<br>消費量<br>(l/h) | 熱効率   | 燃料  | 標準暖房<br>面積 (a) | 製造年度別 経年変化による現在の熱効率および燃料消費量 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|----------------------------------------------------|---------------|--------------|-----------|----------|------|--------------------|-------|-----|----------------|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|                                                    |               |              |           | (kcal/h) | (kW) |                    |       |     |                | 2007                        |       | 2008  |       | 2009  |       | 2010  |       | 2011  |       | 2012  |       | 2013  |       | 2014  |       |
|                                                    |               |              |           |          |      |                    |       |     |                | %                           | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) |
| 24V型                                               | 2007<br>(H19) | 2023<br>(R5) | HK3024TCV | 75,000   | 87.2 | 9.5                | 90.0% | A重油 | 6.6～9.9        | 86.5%                       | 9.9   | 86.7% | 9.9   | 86.9% | 9.8   | 87.2% | 9.8   | 87.4% | 9.8   | 87.6% | 9.8   | 87.8% | 9.7   | 88.0% | 9.7   |
|                                                    |               |              | HK3024TEV | 75,000   | 87.2 | 9.5                | 90.0% | A重油 | 6.6～9.9        | 86.5%                       | 9.9   | 86.7% | 9.9   | 86.9% | 9.8   | 87.2% | 9.8   | 87.4% | 9.8   | 87.6% | 9.8   | 87.8% | 9.7   | 88.0% | 9.7   |
|                                                    |               |              | HK4024TCV | 100,000  | 116  | 12.6               | 90.0% | A重油 | 9.9～13.2       | 86.5%                       | 13.2  | 86.7% | 13.1  | 86.9% | 13.1  | 87.2% | 13.1  | 87.4% | 13.0  | 87.6% | 13.0  | 87.8% | 13.0  | 88.0% | 13.0  |
|                                                    |               |              | HK4024TEV | 100,000  | 116  | 12.6               | 90.0% | A重油 | 9.9～13.2       | 86.5%                       | 13.2  | 86.7% | 13.1  | 86.9% | 13.1  | 87.2% | 13.1  | 87.4% | 13.0  | 87.6% | 13.0  | 87.8% | 13.0  | 88.0% | 13.0  |
|                                                    |               |              | HK5024TCV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 86.5%                       | 16.5  | 86.7% | 16.4  | 86.9% | 16.4  | 87.2% | 16.4  | 87.4% | 16.3  | 87.6% | 16.3  | 87.8% | 16.2  | 88.0% | 16.2  |
|                                                    |               |              | HK5024TEV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 86.5%                       | 16.5  | 86.7% | 16.4  | 86.9% | 16.4  | 87.2% | 16.4  | 87.4% | 16.3  | 87.6% | 16.3  | 87.8% | 16.2  | 88.0% | 16.2  |
|                                                    |               |              | HK5024TFV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 86.5%                       | 16.5  | 86.7% | 16.4  | 86.9% | 16.4  | 87.2% | 16.4  | 87.4% | 16.3  | 87.6% | 16.3  | 87.8% | 16.2  | 88.0% | 16.2  |
|                                                    |               |              | HK6024TCV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 86.5%                       | 19.8  | 86.7% | 19.7  | 86.9% | 19.7  | 87.2% | 19.6  | 87.4% | 19.6  | 87.6% | 19.5  | 87.8% | 19.5  | 88.0% | 19.4  |
|                                                    |               |              | HK6024TEV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 86.5%                       | 19.8  | 86.7% | 19.7  | 86.9% | 19.7  | 87.2% | 19.6  | 87.4% | 19.6  | 87.6% | 19.5  | 87.8% | 19.5  | 88.0% | 19.4  |
|                                                    |               |              | HK6024TFV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 86.5%                       | 19.8  | 86.7% | 19.7  | 86.9% | 19.7  | 87.2% | 19.6  | 87.4% | 19.6  | 87.6% | 19.5  | 87.8% | 19.5  | 88.0% | 19.4  |
| 現行機種HK30型（機器熱効率 90%）へ設備更新した場合の<br>経年変化節減率 ※同等熱出力換算 |               |              |           |          |      |                    |       |     | 3.9%           |                             | 3.7%  |       | 3.4%  |       | 3.2%  |       | 2.9%  |       | 2.7%  |       | 2.4%  |       | 2.2%  |       |       |

【ハウスカナンキ 24V型シリーズ】 2/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

| 製品<br>シリーズ                                         | 製造<br>開始年     | 製造<br>終了年    | 製品型式      | 熱出力      |      | 燃料<br>消費量<br>(l/h) | 熱効率   | 燃料  | 標準暖房<br>面積 (a) | 製造年度別 経年変化による現在の熱効率および燃料消費量 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|----------------------------------------------------|---------------|--------------|-----------|----------|------|--------------------|-------|-----|----------------|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|                                                    |               |              |           | (kcal/h) | (kW) |                    |       |     |                | 2015                        |       | 2016  |       | 2017  |       | 2018  |       | 2019  |       | 2020  |       | 2021  |       | 2022  |       |
|                                                    |               |              |           |          |      |                    |       |     |                | %                           | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) | %     | (l/h) |
| 24V型                                               | 2007<br>(H19) | 2023<br>(R5) | HK3024TCV | 75,000   | 87.2 | 9.5                | 90.0% | A重油 | 6.6～9.9        | 88.2%                       | 9.7   | 88.5% | 9.7   | 88.7% | 9.6   | 88.9% | 9.6   | 89.1% | 9.6   | 89.3% | 9.6   | 89.6% | 9.5   | 89.8% | 9.5   |
|                                                    |               |              | HK3024TEV | 75,000   | 87.2 | 9.5                | 90.0% | A重油 | 6.6～9.9        | 88.2%                       | 9.7   | 88.5% | 9.7   | 88.7% | 9.6   | 88.9% | 9.6   | 89.1% | 9.6   | 89.3% | 9.6   | 89.6% | 9.5   | 89.8% | 9.5   |
|                                                    |               |              | HK4024TCV | 100,000  | 116  | 12.6               | 90.0% | A重油 | 9.9～13.2       | 88.2%                       | 12.9  | 88.5% | 12.9  | 88.7% | 12.9  | 88.9% | 12.8  | 89.1% | 12.8  | 89.3% | 12.8  | 89.6% | 12.7  | 89.8% | 12.7  |
|                                                    |               |              | HK4024TEV | 100,000  | 116  | 12.6               | 90.0% | A重油 | 9.9～13.2       | 88.2%                       | 12.9  | 88.5% | 12.9  | 88.7% | 12.9  | 88.9% | 12.8  | 89.1% | 12.8  | 89.3% | 12.8  | 89.6% | 12.7  | 89.8% | 12.7  |
|                                                    |               |              | HK5024TCV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 88.2%                       | 16.1  | 88.5% | 16.1  | 88.7% | 16.1  | 88.9% | 16.0  | 89.1% | 16.0  | 89.3% | 15.9  | 89.6% | 15.9  | 89.8% | 15.9  |
|                                                    |               |              | HK5024TEV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 88.2%                       | 16.1  | 88.5% | 16.1  | 88.7% | 16.1  | 88.9% | 16.0  | 89.1% | 16.0  | 89.3% | 15.9  | 89.6% | 15.9  | 89.8% | 15.9  |
|                                                    |               |              | HK5024TFV | 125,000  | 145  | 15.8               | 90.0% | A重油 | 13.2～16.5      | 88.2%                       | 16.1  | 88.5% | 16.1  | 88.7% | 16.1  | 88.9% | 16.0  | 89.1% | 16.0  | 89.3% | 15.9  | 89.6% | 15.9  | 89.8% | 15.9  |
|                                                    |               |              | HK6024TCV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 88.2%                       | 19.4  | 88.5% | 19.3  | 88.7% | 19.3  | 88.9% | 19.2  | 89.1% | 19.2  | 89.3% | 19.1  | 89.6% | 19.1  | 89.8% | 19.0  |
|                                                    |               |              | HK6024TEV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 88.2%                       | 19.4  | 88.5% | 19.3  | 88.7% | 19.3  | 88.9% | 19.2  | 89.1% | 19.2  | 89.3% | 19.1  | 89.6% | 19.1  | 89.8% | 19.0  |
|                                                    |               |              | HK6024TFV | 150,000  | 174  | 19.0               | 90.0% | A重油 | 16.5～19.8      | 88.2%                       | 19.4  | 88.5% | 19.3  | 88.7% | 19.3  | 88.9% | 19.2  | 89.1% | 19.2  | 89.3% | 19.1  | 89.6% | 19.1  | 89.8% | 19.0  |
| 現行機種HK30型（機器熱効率 90%）へ設備更新した場合の<br>経年変化節減率 ※同等熱出力換算 |               |              |           |          |      |                    |       |     | 1.9%           |                             | 1.7%  |       | 1.5%  |       | 1.2%  |       | 1.0%  |       | 0.7%  |       | 0.5%  |       | 0.2%  |       |       |