

ネポン 株式会社

【ハウスファンキ 24Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

2020年度 燃効率 燃料消費量 標準暖房面積 備考												製造年度別 経年変化による現在の熱効率および燃料消費量					
製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	2005		2006		2007		
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)	
24Z型	2005 (H17)	2007 (H19)	HK3024TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3024TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK4024TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4024TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK5024TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5			86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5			86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5			86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5024TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK6024TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8			86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8			86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8			86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6024TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形		86.1%	19.9	86.3%	19.8	86.5%	19.8
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											4.4%		4.1%		3.9%		