

ネパソ株式会社

【バスカノン 25、25E型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1997	1998	1999	2000	2001	2002	2003	2004	2005									
											% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)	% (l/h)								
25型 ・ 25E型	1997 (H9)	2005 (H17)	HK1525SC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525SE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525TC	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525TE	38,000	44.2	4.9	88.0%	A重油	3.3～4.95		82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525TCP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形	82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK1525TEP	38,000	44.2	4.9	88.0%	A重油	3.3～4.95	静音形	82.3%	5.3	82.5%	5.2	82.7%	5.2	83.0%	5.2	83.2%	5.2	83.4%	5.2	83.6%	5.2	83.8%	5.2	84.1%	5.2
			HK2025SC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025SE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025SR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6		82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TR	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	スイング形	82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TCS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TES	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK2025TRS	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形	82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9	83.2%	6.9	83.4%	6.8	83.6%	6.8	83.8%	6.8	84.1%	6.8
			HK3025SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025SR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形	82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TR	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	スイング形	82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TCS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TES	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TFS	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形	82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TCE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TEE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK3025TFE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9		82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	84.1%	10.2
			HK4025TC	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TE	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TF	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TR5	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 50Hz	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TR6	100,000	116	13.0	88.0%	A重油	9.9～13.2	スイング形, 60Hz	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TCS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TES	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TFS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TRS	100,000	116	13.0	88.0%	A重油	9.9～13.2	静音形	82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TCE	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TEE	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK4025TFE	100,000	116	13.0	88.0%	A重油	9.9～13.2		82.3%	13.9	82.5%	13.8	82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6	84.1%	13.6
			HK5025TC	125,000	145	16.2	88.0%	A重油	13.2～16.5		82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5025TE	125,000	145	16.2	88.0%	A重油	13.2～16.5		82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5025TF	125,000	145	16.2	88.0%	A重油	13.2～16.5		82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
			HK5025TCS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0
HK5025TES	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0			
HK5025TFS	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形	82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0	84.1%	17.0			
HK5025TCE	125,000	145	16.2	88.0%																								