

ネポン株式会社

【ハウスカネ 25Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																					
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005					
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)				
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9			
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9			
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9		
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9			
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9			
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9			
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9		
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9		
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9		
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形			84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9		
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2			
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2			
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2			
			HK4025TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形			84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3	85.6%	13.3	85.8%	13.3	86.1%	13.2		
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形					84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	
			HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	
			HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9	
			HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
			HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形					84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0	85.6%	20.0	85.8%	19.9	86.1%	19.9
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											6.3%		6.1%		5.8%		5.6%		5.4%		5.1%		4.9%		4.6%		4.4%					