

ネ ポ ン 株式会社

【ハウスオンキ 27V型シリーズ】 1/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2007		2008		2009		2010		2011		2012		2013		2014	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
27V型	2007 (H19)	2023 (R5)	HK1527TCV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0										
			HK1527TEV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0										
			HK2027TCV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5
			HK2027TEV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6		86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5
			HK2027TRV	50,000	58.1	6.3	90.0%	A重油	4.95~6.6	スینگ [®] 形	86.5%	6.6	86.7%	6.6	86.9%	6.6	87.2%	6.5	87.4%	6.5	87.6%	6.5	87.8%	6.5	88.0%	6.5
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スینگ [®] 形	86.5%	9.9	86.7%	9.9	86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7
			HK4027TCV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4027TEV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4027TFV	100,000	116	12.6	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4027FRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スینگ [®] 形, 50Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4027GRV	100,000	116	12.6	90.0%	A重油	9.9~13.2	スینگ [®] 形, 60Hz	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK4027TYV	100,000	116	12.6	90.0%	A重油	9.9~13.2	低床スینگ [®] 形	86.5%	13.2	86.7%	13.1	86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2
			HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
			HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
			HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											3.9%		3.7%		3.4%		3.2%		2.9%		2.7%		2.4%		2.2%	

【ハウスオンキ 27V型シリーズ】 2/2

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						2015		2016		2017		2018		2019		2020		2021		2022	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
27V型	2007 (H19)	2023 (R5)	HK2027TCV	50,000	58.1	6.3	90.0%	A重油	4.95～6.6		88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3
			HK2027TEV	50,000	58.1	6.3	90.0%	A重油	4.95～6.6		88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3
			HK2027TRV	50,000	58.1	6.3	90.0%	A重油	4.95～6.6	スイング形	88.2%	6.5	88.5%	6.4	88.7%	6.4	88.9%	6.4	89.1%	6.4	89.3%	6.4	89.6%	6.4	89.8%	6.3
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	88.2%	9.7	88.5%	9.7	88.7%	9.6	88.9%	9.6	89.1%	9.6	89.3%	9.6	89.6%	9.5	89.8%	9.5
			HK4027TCV	100,000	116	12.6	90.0%	A重油	9.9～13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK4027TEV	100,000	116	12.6	90.0%	A重油	9.9～13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK4027TFV	100,000	116	12.6	90.0%	A重油	9.9～13.2		88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK4027FRV	100,000	116	12.6	90.0%	A重油	9.9～13.2	スイング形, 50Hz	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK4027GRV	100,000	116	12.6	90.0%	A重油	9.9～13.2	スイング形, 60Hz	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK4027TYV	100,000	116	12.6	90.0%	A重油	9.9～13.2	低床スイング形	88.2%	12.9	88.5%	12.9	88.7%	12.9	88.9%	12.8	89.1%	12.8	89.3%	12.8	89.6%	12.7	89.8%	12.7
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2～16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2～16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2～16.5		88.2%	16.1	88.5%	16.1	88.7%	16.1	88.9%	16.0	89.1%	16.0	89.3%	15.9	89.6%	15.9	89.8%	15.9
			HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5～19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0
			HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5～19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0
			HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5～19.8		88.2%	19.4	88.5%	19.3	88.7%	19.3	88.9%	19.2	89.1%	19.2	89.3%	19.1	89.6%	19.1	89.8%	19.0
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											1.9%		1.7%		1.5%		1.2%		1.0%		0.7%		0.5%		0.2%	