

ネポソ株式会社

【ハウスファンキ 27Z型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
27Z型	2005 (H17)	2007 (H19)	HK1527TCZ	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK1527TEZ	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK2027TCZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6		86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TEZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6		86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TRZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	スイング形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TCSZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TESZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2027TRSZ	50,000	58.1	6.4	90.0%	A重油	4.95～6.6	静音形	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK3027TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3027TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK4027TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 50Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング形, 60Hz	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK4027TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	86.1%	13.2	86.3%	13.2	86.5%	13.2
			HK5027TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK5027TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	86.1%	16.6	86.3%	16.5	86.5%	16.5
			HK6027TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
			HK6027TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	86.1%	19.9	86.3%	19.8	86.5%	19.8
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											4.4%		4.1%		3.9%	