

ネボン株式会社

【ハウスコナ 8.10型シリーズ】

2023 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
8 型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95			79.2%	4.6	79.5%	4.6	79.7%	4.6							
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95			79.2%	4.6	79.5%	4.6	79.7%	4.6							
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			79.2%	7.2	79.5%	7.2	79.7%	7.2							
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6			79.2%	7.2	79.5%	7.2	79.7%	7.2							
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9			79.2%	10.8	79.5%	10.8	79.7%	10.7							
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9～13.2			79.2%	12.5	79.5%	12.5	79.7%	12.4							
HK508TC	125,000	145	16.2	88.0%	A重油	13.2～16.5			79.2%	18.0	79.5%	17.9	79.7%	17.9										
HK608TC	150,000	174	19.4	88.0%	A重油	16.5～19.8			79.2%	21.6	79.5%	21.5	79.7%	21.5										
10 型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95						79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK160SC	32,000	37.2	4.2	88.0%	A重油	3.3～4.95						79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK160TE	32,000	37.2	4.2	88.0%	A重油	3.3～4.95						79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK160TC	32,000	37.2	4.2	88.0%	A重油	3.3～4.95						79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK160TEP	32,000	37.2	4.2	88.0%	A重油	3.3～4.95	静音形					79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK160TCP	32,000	37.2	4.2	88.0%	A重油	3.3～4.95	静音形					79.7%	4.6	79.9%	4.6	80.1%	4.6	80.3%	4.5		
			HK210SE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6						79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK210SC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6						79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK210TE	50,000	58.1	6.5	88.0%	A重油	4.95～6.6						79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK210TC	50,000	58.1	6.5	88.0%	A重油	4.95～6.6						79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK210TEP	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形					79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK210TCP	50,000	58.1	6.5	88.0%	A重油	4.95～6.6	静音形					79.7%	7.2	79.9%	7.1	80.1%	7.1	80.3%	7.1		
			HK310SE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9						79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310SC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9						79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TE	75,000	87.2	9.7	88.0%	A重油	6.6～9.9						79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TC	75,000	87.2	9.7	88.0%	A重油	6.6～9.9						79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TF	75,000	87.2	9.7	88.0%	A重油	6.6～9.9						79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TEP	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形					79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TCP	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	静音形					79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TCM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー					79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TEM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー					79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK310TFM	75,000	87.2	9.7	88.0%	A重油	6.6～9.9	システムバナー					79.7%	10.7	79.9%	10.7	80.1%	10.7	80.3%	10.6		
			HK410TE	87,000	101	11.3	88.0%	A重油	9.9～13.2						79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TC	87,000	101	11.3	88.0%	A重油	9.9～13.2						79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TF	87,000	101	11.3	88.0%	A重油	9.9～13.2						79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TEP	87,000	101	11.3	88.0%	A重油	9.9～13.2	静音形					79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TCP	87,000	101	11.3	88.0%	A重油	9.9～13.2	静音形					79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TCM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー					79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TEM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー					79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK410TFM	87,000	101	11.3	88.0%	A重油	9.9～13.2	システムバナー					79.7%	12.4	79.9%	12.4	80.1%	12.4	80.3%	12.3		
			HK510TC	125,000	145	16.2	88.0%	A重油	13.2～16.5						79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7		
			HK510TCP	125,000	145	16.2	88.0%	A重油	13.2～16.5	静音形					79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7		
			HK510TCM	125,000	145	16.2	88.0%	A重油	13.2～16.5	システムバナー					79.7%	17.9	79.9%	17.8	80.1%	17.8	80.3%	17.7		
			HK610TC	150,000	174	19.4	88.0%	A重油	16.5～19.8						79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3		
			HK610TCP	150,000	174	19.4	88.0%	A重油	16.5～19.8	静音形					79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3		
			HK610TCM	150,000	174	19.4	88.0%	A重油	16.5～19.8	システムバナー					79.7%	21.5	79.9%	21.4	80.1%	21.3	80.3%	21.3		
			HK810TC	200,000	233	25.9	88.0%	A重油	19.8～26.4						79.7%	28.6	79.9%	28.5	80.1%	28.5	80.3%	28.4		
			現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											12.0%		11.7%		11.5%		11.2%		11.0%		10.7%