

ネポン株式会社

【ハウスカキ 8,10型シリーズ】

2024年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988					
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)				
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			79.0%	4.6	79.2%	4.6	79.5%	4.6									
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			79.0%	4.6	79.2%	4.6	79.5%	4.6									
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			79.0%	7.2	79.2%	7.2	79.5%	7.2									
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			79.0%	7.2	79.2%	7.2	79.5%	7.2									
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			79.0%	10.8	79.2%	10.8	79.5%	10.8									
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			79.0%	10.8	79.2%	10.8	79.5%	10.8									
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			79.0%	10.8	79.2%	10.8	79.5%	10.8									
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			79.0%	10.8	79.2%	10.8	79.5%	10.8									
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			79.0%	10.8	79.2%	10.8	79.5%	10.8									
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2			79.0%	12.6	79.2%	12.5	79.5%	12.5									
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			79.0%	12.6	79.2%	12.5	79.5%	12.5									
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			79.0%	12.6	79.2%	12.5	79.5%	12.5									
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5			79.0%	18.0	79.2%	18.0	79.5%	17.9									
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8			79.0%	21.6	79.2%	21.6	79.5%	21.5									
			10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95						79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6	
						HK160SC	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6
						HK160TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6
HK160TC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6			
HK160TEP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6			
HK160TCP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					79.5%	4.6	79.7%	4.6	79.9%	4.6	80.1%	4.6			
HK210SE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK210SC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK210TE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK210TC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK210TEP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK210TCP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					79.5%	7.2	79.7%	7.2	79.9%	7.1	80.1%	7.1			
HK310SE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310SC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TF	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TEP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TCP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TCM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムバナー					79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TEM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムバナー					79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK310TFM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムバナー					79.5%	10.8	79.7%	10.7	79.9%	10.7	80.1%	10.7			
HK410TE	87,000	101				11.3	88.0%	A重油	9.9~13.2							79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4			
HK410TC	87,000	101				11.3	88.0%	A重油	9.9~13.2							79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4			
HK410TF	87,000	101				11.3	88.0%	A重油	9.9~13.2							79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4			
HK410TEP	87,000	101				11.3	88.0%	A重油	9.9~13.2		静音形					79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4			
HK410TCP	87,000	101	11.3	88.0%	A重油	9.9~13.2		静音形					79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4						
HK410TCM	87,000	101	11.3	88.0%	A重油	9.9~13.2		システムバナー					79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4						
HK410TEM	87,000	101	11.3	88.0%	A重油	9.9~13.2		システムバナー					79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4						
HK410TFM	87,000	101	11.3	88.0%	A重油	9.9~13.2		システムバナー					79.5%	12.5	79.7%	12.4	79.9%	12.4	80.1%	12.4						
HK510TC	125,000	145	16.2	88.0%	A重油	13.2~16.5							79.5%	17.9	79.7%	17.9	79.9%	17.8	80.1%	17.8						
HK510TCP	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形					79.5%	17.9	79.7%	17.9	79.9%	17.8	80.1%	17.8						
HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5		システムバナー					79.5%	17.9	79.7%	17.9	79.9%	17.8	80.1%	17.8						
HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8							79.5%	21.5	79.7%	21.5	79.9%	21.4	80.1%	21.3						
HK610TCP	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形					79.5%	21.5	79.7%	21.5	79.9%	21.4	80.1%	21.3						
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8		システムバナー					79.5%	21.5	79.7%	21.5	79.9%	21.4	80.1%	21.3						
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4							79.5%	28.7	79.7%	28.6	79.9%	28.5	80.1%	28.5						
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											12.2%	12.0%	11.7%	11.5%	11.2%	11.0%										