

ネポン株式会社

【ハウスコンキ 17, 22型シリーズ】

2024 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						1995		1996		1997			
						%	(l/h)	%	(l/h)	%	(l/h)							
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			83.6%	5.2	83.9%	5.2	84.1%	5.2	
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			83.6%	5.2	83.9%	5.2	84.1%	5.2	
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			83.6%	5.2	83.9%	5.2	84.1%	5.2	
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			83.6%	5.2	83.9%	5.2	84.1%	5.2	
			HK1522TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形			83.6%	5.2	83.9%	5.2	84.1%	5.2
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形			83.6%	5.2	83.9%	5.2	84.1%	5.2
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0				83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形			83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形			83.6%	6.8	83.9%	6.8	84.1%	6.8
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				83.6%	10.2	83.9%	10.2	84.1%	10.2
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9~13.2				83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9~13.2				83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9~13.2				83.6%	13.6	83.9%	13.6	84.1%	13.6
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2~16.5				83.6%	17.0	83.9%	17.0	84.1%	16.9
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				83.6%	17.0	83.9%	17.0	84.1%	16.9
HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			83.6%	17.0	83.9%	17.0	84.1%	16.9			
HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			83.6%	17.0	83.9%	17.0	84.1%	16.9			
HK5017TF	125,000	145	15.8	90.0%	A重油	13.2~16.5				83.6%	17.0	83.9%	17.0	84.1%	16.9			
HK6022TC	150,000	174	19.0	90.0%	A重油	16.5~19.8				83.6%	20.4	83.9%	20.4	84.1%	20.3			
HK6022TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				83.6%	20.4	83.9%	20.4	84.1%	20.3			
HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			83.6%	20.4	83.9%	20.4	84.1%	20.3			
HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			83.6%	20.4	83.9%	20.4	84.1%	20.3			
HK6017TF	150,000	174	19.0	90.0%	A重油	16.5~19.8				83.6%	20.4	83.9%	20.4	84.1%	20.3			
HK8022TF	200,000	233	19.0	90.0%	A重油	19.8~26.4				83.6%	27.3	83.9%	27.2	84.1%	27.1			
現行機種HK30型 (機器熱効率 90%)へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											7.1%		6.8%		6.6%			