

ネボン株式会社
【ハウスカオンキ 23型シリーズ】

2024 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量													
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2	
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形			82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				82.7%	10.3	83.0%	10.3	83.2%	10.3	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9~13.2				82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9~13.2				82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9~13.2				82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形			82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形			82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2				82.7%	13.8	83.0%	13.7	83.2%	13.7	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2~16.5				82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2~16.5				82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0
HK5023TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0			
HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形			82.7%	17.2	83.0%	17.2	83.2%	17.1	83.4%	17.1	83.6%	17.0	83.8%	17.0			
HK6023TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
HK6023TE	150,000	174	19.4	88.0%	A重油	16.5~19.8				82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
HK6023TF	150,000	174	19.4	88.0%	A重油	16.5~19.8				82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
HK6023TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形			82.7%	20.7	83.0%	20.6	83.2%	20.6	83.4%	20.5	83.6%	20.5	83.8%	20.4			
現行機種HK30型（機器熱効率 90%）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											8.1%	7.8%	7.6%	7.3%	7.1%	6.8%								