## ネポン株式会社

【ハウスカオンキ 25, 25E型シリース<sup>\*</sup>】 2024 年度 熱効率/燃料消費量 経年変化一覧表 製造年度別 経年変化による現在の熱効率および燃料消費量 燃料 製诰 製造 熱出力 標準暖房 製品型式 消費量 熱効率 備考 1997 1998 1999 2000 2001 2002 2003 2004 2005 シリース 開始年 終了年 面積(a) (kcal/h) (1/h) % (I/h) % (I/h) (kW) % (1/h) % (1/h) % (1/h) % (1/h) % (I/h) % (1/h) HK1525SC 38, 000 44. 2 4. 9 88.0% A 重油 3.3~4.95 82. 1% 5. 3 | 82. 3% 5. 3 | 82. 5% 5. 2 | 82. 7% 5. 2 | 83. 0% 5. 2 | 83. 2% 5. 2 | 83. 4% 5. 2 | 83. 6% 5. 2 | 83. 8% 5. 2 5. 2 82. 7% 5. 2 83. 0% 5. 2 83. 2% 5. 2 83. 4% 5. 2 83. 6% 5. 2 83. 8% 5. 2 HK1525SE 44. 2 82. 1% 5. 3 82. 3% 5. 3 82. 5% 38 000 4 9 88.0% | A 重油 | 3.3~4.95 HK1525TC 38,000 44. 2 88.0% A重油 3.3~4.95 82.1% 5. 3 82. 3% 5. 3 82. 5% 5. 2 82. 7% 5. 2 83. 0% 5. 2 83. 2% 5. 2 83. 4% 5. 2 83. 6% 5. 2 83. 8% 5. 2 49 82. 5% HK1525TE 38, 000 44. 2 4 9 88.0% A重油 3.3~4.95 82. 1% 5. 3 82.3% 5. 3 5. 2 82. 7% 5. 2 83. 0% 5. 2 83. 2% 5. 2 83. 4% 5. 2 83. 6% 5. 2 83. 8% 5. 2 HK1525TCP 38, 000 44. 2 88.0% A重油 3.3~4.95 静音形 82. 1% 5.3 82.3% 5. 3 82. 5% 5. 2 82. 7% 5. 2 83.0% 5. 2 83. 2% 5. 2 83.4% 5. 2 83.6% 5. 2 49 83 8% 5 2 HK1525TEP 38, 000 44. 2 4. 9 88.0% A重油 3.3~4.95 静音形 82. 1% 5. 3 82.3% 5. 3 82.5% 5. 2 82. 7% 5. 2 83. 0% 5. 2 83. 2% 5. 2 83.4% 5. 2 83.6% 5. 2 | 83. 8% | 5. 2 HK2025SC 50 000 58 1 6.5 88.0% A重油 4.95~6.6 82.1% 6 9 82.3% 6 9 82. 5% 6. 9 82. 7% 6. 9 83.0% 6.9 83. 2% 6. 9 83.4% 6.8 83.6% 6. 8 83. 8% 6.8 HK2025SE 50,000 58. 1 88.0% A重油 4.95~6.6 82. 1% 6. 9 82.3% 6. 9 82. 5% 6.9 82. 7% 6. 9 83.0% 6. 9 83. 2% 6. 9 83.4% 6.8 83.6% 6.8 6.5 83.8% HK2025SR 50,000 58. 1 6.5 88.0% A重油 4.95∼6.6 82.1% 6.9 82.3% 6. 9 82. 5% 6. 9 82. 7% 6.9 83.0% 6. 9 83. 2% 6.9 83.4% 6.8 83.6% 6.8 83.8% 6.8 58. 1 50,000 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 8 83. 8% 6. 8 HK2025TC 6. 5 88.0% | A 重油 | 4.95~6.6 82. 1% 6. 9 82.3% 6. 9 83.4% 6.8 83.6% HK2025TE 50,000 58. 1 6. 5 88.0% A重油 4.95~6.6 82.1% 6. 9 82.3% 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 9 83. 4% 6.8 83.6% 6. 8 83. 8% 6. 8 6.8 83.8% 6.8 HK2025TR 50,000 58. 1 6. 5 88.0% A重油 4.95~6.6 スイング・形 82. 1% 6. 9 82. 3% 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 9 83. 4% 6.8 83.6% 50,000 58. 1 6. 5 88.0% A 重油 4.95~6.6 静音形 82. 1% 6. 9 82.3% 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 9 83. 4% 6.8 83.6% 6.8 83.8% 6.8 HK2025TCS HK2025TES 50,000 58 1 6 5 88.0% A 重油 4.95~6.6 静音形 82. 1% 6. 9 82. 3% 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 9 83. 4% 6. 8 83. 6% 6. 8 83. 8% 6. 8 HK2025TRS 50 000 58. 1 6. 5 88.0% A 重油 4.95~6.6 静音形 82. 1% 6. 9 82. 3% 6. 9 82. 5% 6. 9 82. 7% 6. 9 83. 0% 6. 9 83. 2% 6. 9 83. 4% 6. 8 | 83. 6% | 6. 8 | 83. 8% | 6. 8 HK3025SC 75, 000 87. 2 9.7 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10.4 82.7% 10.3 83.0% 10.3 83.2% 10.3 83.4% 10.3 83.6% 10.2 83.8% 10.2 HK3025SE 75,000 87. 2 9.7 88.0% A 重油 6.6~9.9 82. 1% | 10. 4 | 82. 3% | 10. 4 | 82. 5% | 10. 4 | 82. 7% | 10. 3 | 83. 0% | 10. 3 | 83. 2% | 10. 3 | 83. 4% | 10. 3 | 83. 6% | 10. 2 | 83. 8% | 10. 2 HK3025SR 87. 2 9.7 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10. 4 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 83. 6% 10. 2 83. 8% 10. 2 75, 000 スイング形 HK3025TC 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10. 4 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 83. 6% 10. 2 83. 8% 10. 2 75,000 87. 2 9 7 HK3025TE 75, 000 87. 2 9. 7 88.0% A重油 6.6~9.9 82. 1% 10. 4 82.3% 10.4 82.5% 10.4 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 83. 6% 10. 2 83. 8% 10. 2 HK3025TF 75, 000 87. 2 9. 7 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10. 4 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 83.6% 10.2 83. 8% 10. 2 HK3025TR 82. 7% 10. 3 83.0% 10.3 83.2% 10.3 75, 000 87. 2 9.7 88.0% A 重油 6.6~9.9 スイング形 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10. 4 83. 4% 10. 3 83. 6% 10. 2 83. 8% 10. 2 75,000 82. 1% 10. 4 82.5% 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 83.6% 10.2 83.8% 10.2 HK3025TCS 87. 2 88.0% | A重油 | 6.6~9.9 静音形 82. 3% 10. 4 10.4 HK3025TES 75,000 87. 2 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10.4 82. 7% 10. 3 83.0% 10.3 83. 2% 10. 3 83. 4% 10. 3 83.6% 10. 2 静音形 83. 8% 10. 2 HK3025TFS 75, 000 87. 2 9 7 88.0% A 重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10. 4 82. 7% 10. 3 83.0% 10.3 83.2% 10.3 83, 4% 10, 3 83.6% 10.2 83.8% 10.2 静音形 75, 000 82. 1% 10. 4 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83.6% 10.2 83.8% 10.2 HK3025TCE 87 2 9 7 88.0% A重油 6.6~9.9 82. 3% 10. 4 82.5% 10.4 83. 4% 10. 3 82. 3% 10. 4 82. 5% 82. 7% 10. 3 83. 0% 10. 3 83. 2% 10. 3 83. 4% 10. 3 HK3025TEE 75, 000 87. 2 9.7 88.0% A重油 6.6~9.9 82.1% 10.4 10.4 83.6% 10.2 83.8% 10.2 HK3025TFE 75,000 87. 2 9. 7 88.0% A重油 6.6~9.9 82. 1% 10. 4 82. 3% 10. 4 82. 5% 10.4 82. 7% 10. 3 | 83. 0% 10. 3 | 83. 2% 10. 3 | 83. 4% 10. 3 | 83. 6% 10. 2 | 83. 8% 10. 2 1997 HK4025TC 100,000 116 13. 0 88.0% A重油 9.9~13.2 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13.8 82, 7% 13, 8 83, 0% 13, 7 83, 2% 13, 7 83, 4% 13, 7 83, 6% 13, 6 83, 8% 13, 6 2005 (H9) (H17)83. 0% 13. 7 83. 2% 13. 7 83. 4% 13. 7 83. 6% 13. 6 83. 8% 13. 6 HK4025TE 100,000 116 13 0 88.0% A 重油 9.9~13.2 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 25E型 HK4025TF 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83. 0% 13. 7 83. 2% 13. 7 83. 4% 13. 7 100.000 116 13.0 88.0% A重油 9.9~13.2 82. 1% 13. 9 83.6% 13.6 83.8% 13.6 HK4025TR5 100,000 116 | 13.0 | 88.0% | A 重油 | 9.9~13.2 | スイング 形, 50Hz 82. 1% 13. 9 82. 3% | 13. 9 | 82. 5% | 13. 8 | 82. 7% | 13. 8 | 83. 0% | 13. 7 | 83. 2% | 13. 7 | 83. 4% | 13. 7 | 83. 6% | 13. 6 | 83. 8% | 13. 6 HK4025TR6 100,000 116 13.0 88.0% A 重油 9.9~13.2 スインケ 形、60Hz 82, 1% | 13, 9 | 82, 3% | 13, 9 | 82, 5% | 13, 8 | 82, 7% | 13, 8 | 83, 0% | 13, 7 | 83, 2% | 13, 7 | 83, 4% | 13, 7 | 83. 6% 13. 6 83. 8% 13. 6 82. 5% 13. 8 82. 7% 13. 8 83. 0% 13. 7 83. 2% 13. 7 83. 4% 13. 7 HK4025TCS 100,000 116 13.0 88.0% A 重油 9.9~13.2 静音形 82. 1% 13. 9 82. 3% 13. 9 83. 6% 13. 6 83. 8% 13. 6 83.0% 13.7 83.2% 13.7 83.4% 13.7 HK4025TES 100.000 116 13.0 88.0% A重油 9.9~13.2 静音形 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83. 6% 13. 6 83. 8% 13. 6 HK4025TFS 100.000 116 13.0 88.0% A重油 9.9~13.2 静音形 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83. 0% 13. 7 | 83. 2% 13. 7 | 83. 4% 13. 7 83. 6% 13. 6 83. 8% 13. 6 HK4025TRS 100,000 116 13.0 88.0% A重油 9.9~13.2 静音形 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83.0% 13.7 83.2% 13.7 83. 4% 13. 7 83.6% 13.6 83.8% 13.6 HK4025TCE 100,000 116 13.0 88.0% A 重油 9.9~13.2 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83.0% 13.7 83. 2% 13. 7 83, 4% 13, 7 83.6% 13.6 83. 8% 13. 6 100,000 88.0% A重油 9.9~13.2 82. 1% 13. 9 82. 3% 13. 9 82. 5% 13. 8 82. 7% 13. 8 83. 0% 13. 7 83. 2% 13. 7 83. 4% 13. 7 83.6% 13.6 83.8% 13.6 HK4025TEE 116 13.0 HK4025TFE 100,000 116 13.0 88.0% | A 重油 | 9.9~13.2 82. 1% 13. 9 82. 3% | 13. 9 | 82. 5% | 13. 8 82. 7% 13. 8 83. 0% | 13. 7 | 83. 2% | 13. 7 83. 4% 13. 7 83. 6% 13. 6 83. 8% 13. 6 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83.6% 17.0 83.8% 17.0 HK5025TC 125, 000 145 | 16.2 | 88.0% | A 重油 | 13.2~16.5 125, 000 88.0% A重油 13.2~16.5 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83.6% 17.0 83.8% 17.0 HK5025TE 145 16. 2 HK5025TF 125, 000 145 16.2 88.0% A重油 13.2~16.5 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83. 6% 17. 0 83. 8% 17. 0 HK5025TCS 125, 000 145 16. 2 88.0% A重油 13.2~16.5 静音形 82. 1% | 17. 4 | 82. 3% | 17. 3 | 82. 5% | 17. 3 | 82. 7% | 17. 2 | 83. 0% | 17. 2 | 83. 2% | 17. 1 | 83. 4% | 17. 1 | 83. 6% | 17. 0 | 83. 8% | 17. 0 16.2 88.0% A重油 13.2~16.5 静音形 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83. 6% 17. 0 83. 8% 17. 0 HK5025TES 125,000 145 16.2 88.0% A 重油 13.2~16.5 静音形 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83. 6% 17. 0 83. 8% 17. 0 HK5025TFS 125 000 145 HK5025TCE 125,000 145 16.2 88.0% A 重油 13.2~16.5 82. 1% | 17. 4 | 82. 3% | 17. 3 | 82. 5% | 17. 3 | 82. 7% | 17. 2 | 83. 0% | 17. 2 | 83. 2% | 17. 1 | 83. 4% | 17. 1 | 83. 6% | 17. 0 | 83. 8% | 17. 0 HK5025TEE 145 16.2 88.0% A重油 13.2~16.5 82. 1% | 17. 4 | 82. 3% | 17. 3 | 82. 5% | 17. 3 | 82. 7% | 17. 2 | 83. 0% | 17. 2 | 83. 2% | 17. 1 | 83. 4% | 17. 1 | 83. 6% | 17. 0 | 83. 8% | 17. 0 125, 000 125,000 145 82. 1% 17. 4 82. 3% 17. 3 82. 5% 17. 3 82. 7% 17. 2 83. 0% 17. 2 83. 2% 17. 1 83. 4% 17. 1 83. 6% 17. 0 83. 8% 17. 0 HK5025TFE 16.2 88.0% A 重油 13.2~16.5 HK6025TC 174 88.0% A重油 16.5~19.8 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 83, 6% 20, 5 83, 8% 20, 4 150 000 19 4 HK6025TE 150,000 174 19.4 88.0% A 重油 16.5~19.8 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 83. 6% 20. 5 83. 8% 20. 4 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 HK6025TF 150,000 174 19.4 88.0% A重油 16.5~19.8 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 83.6% 20.5 83.8% 20.4 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 HK6025TCS 150,000 174 19.4 88.0% | A 重油 | 16.5~19.8 | 静音形 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 83.6% 20.5 174 88.0% A 重油 16.5~19.8 静音形 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83, 4% 20, 5 83.6% 20.5 HK6025TES 150 000 19 4 HK6025TFS 150,000 174 19.4 88.0% A 重油 16.5~19.8 静音形 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83, 4% 20, 5 83. 6% 20. 5 83. 8% 20. 4 HK6025TCE 150,000 174 19.4 88.0% A 重油 16.5~19.8 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 83. 6% 20. 5 83. 8% 20. 4 19.4 88.0% A重油 16.5~19.8 82. 3% 20. 8 82. 5% 20. 7 82. 7% 20. 7 83. 0% 20. 6 83. 2% 20. 6 83. 4% 20. 5 83. 6% 20. 5 83. 8% 20. 4 HK6025TEE 150,000 174 82. 1% 20. 8 HK6025TFE 150,000 174 19.4 88.0% A重油 16.5~19.8 82. 1% 20. 8 82. 3% 20. 8 82. 5% 20. 7 82, 7% 20, 7 83, 0% 20, 6 83, 2% 20, 6 83, 4% 20, 5 83, 6% 20, 5 83, 8% 20, 4 現行機種HK30型(機器熱効率 90%) へ設備更新した場合の 8.8% 8.6% 8.3% 8.1% 7.8% 7.6% 7.3% 7.1% 6.8% 経年変化節減率 ※同等熱出力換算