

ネポン株式会社

【ハウスカオンキ 24型シリーズ】

2026 年度

熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量 ※1					
											2005		2006		2007	
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9		83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TE	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9		83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TF	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9		83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TR	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9	スイング 形	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TCS	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9	静音形	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TES	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9	静音形	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK3024TFS	75,000	87.2	9.7	88.0%	A 重油	6.6～9.9	静音形	83.4%	10.3	83.6%	10.2	83.8%	10.2
			HK4024TC	100,000	116	13.0	88.0%	A 重油	9.9～13.2		83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TE	100,000	116	13.0	88.0%	A 重油	9.9～13.2		83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TF	100,000	116	13.0	88.0%	A 重油	9.9～13.2		83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TR5	100,000	116	13.0	88.0%	A 重油	9.9～13.2	スイング 形,50Hz	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TR6	100,000	116	13.0	88.0%	A 重油	9.9～13.2	スイング 形,60Hz	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TCS	100,000	116	13.0	88.0%	A 重油	9.9～13.2	静音形	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TES	100,000	116	13.0	88.0%	A 重油	9.9～13.2	静音形	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TFS	100,000	116	13.0	88.0%	A 重油	9.9～13.2	静音形	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK4024TRS	100,000	116	13.0	88.0%	A 重油	9.9～13.2	静音形	83.4%	13.7	83.6%	13.6	83.8%	13.6
			HK5024TC	125,000	145	16.2	88.0%	A 重油	13.2～16.5		83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5024TE	125,000	145	16.2	88.0%	A 重油	13.2～16.5		83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5024TF	125,000	145	16.2	88.0%	A 重油	13.2～16.5		83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5024TCS	125,000	145	16.2	88.0%	A 重油	13.2～16.5	静音形	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5024TES	125,000	145	16.2	88.0%	A 重油	13.2～16.5	静音形	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK5024TFS	125,000	145	16.2	88.0%	A 重油	13.2～16.5	静音形	83.4%	17.1	83.6%	17.0	83.8%	17.0
			HK6024TC	150,000	174	19.4	88.0%	A 重油	16.5～19.8		83.4%	20.5	83.6%	20.5	83.8%	20.4
			HK6024TE	150,000	174	19.4	88.0%	A 重油	16.5～19.8		83.4%	20.5	83.6%	20.5	83.8%	20.4
			HK6024TF	150,000	174	19.4	88.0%	A 重油	16.5～19.8		83.4%	20.5	83.6%	20.5	83.8%	20.4
			HK6024TCS	150,000	174	19.4	88.0%	A 重油	16.5～19.8	静音形	83.4%	20.5	83.6%	20.5	83.8%	20.4
			HK6024TES	150,000	174	19.4	88.0%	A 重油	16.5～19.8	静音形	83.4%	20.5	83.6%	20.5	83.8%	20.4
			HK6024TFS	150,000	174	19.4	88.0%	A 重油	16.5～19.8	静音形	83.4%	20.5	83.6%	20.5	83.8%	20.4
現行機種HK30・29型（機器熱効率 90% ）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											7.3%		7.1%		6.8%	

※1 製造年度を使用開始年度とみなし、毎年一定の使用期間がある場合の経年変化目安とする