

ネポン 株式会社

【ハウスカオンキ 24Z型シリーズ】

2026 年度

熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積（a）	備考	製造年度別 経年変化による現在の熱効率および燃料消費量 ※1					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24Z型	2005 (H17)	2007 (H19)	HK3024TCZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TEZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TFZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TRZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	スイング 形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TCSZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TESZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3024TFSZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK4024TCZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TEZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TFZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TR5Z	100,000	116	12.7	90.0%	A 重油	9.9～13.2	スイング 形,50Hz	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TR6Z	100,000	116	12.7	90.0%	A 重油	9.9～13.2	スイング 形,60Hz	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TCSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TESZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TFSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4024TRSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK5024TCZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5024TEZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5024TFZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5024TCSZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5024TESZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5024TFSZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK6024TCZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6024TEZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6024TFZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6024TCSZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6024TESZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6024TFSZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
現行機種HK30・29型（機器熱効率 90% ）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											5.1%		4.9%		4.6%	

※1 製造年度を使用開始年度とみなし、毎年一定の使用期間がある場合の経年変化目安とする