

ネボン株式会社

【ハウスカオンキ 27Z型シリーズ】

2026 年度

熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量 ※1					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
27Z型	2005 (H17)	2007 (H19)	HK1527TCZ	38,000	44.2	4.8	90.0%	A 重油	3.3～4.95		85.4%	5.1	85.6%	5.1	85.8%	5.0
			HK1527TEZ	38,000	44.2	4.8	90.0%	A 重油	3.3～4.95		85.4%	5.1	85.6%	5.1	85.8%	5.0
			HK2027TCZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6		85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK2027TEZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6		85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK2027TRZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6	スイング 形	85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK2027TCSZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6	静音形	85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK2027TESZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6	静音形	85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK2027TRSZ	50,000	58.1	6.4	90.0%	A 重油	4.95～6.6	静音形	85.4%	6.7	85.6%	6.7	85.8%	6.6
			HK3027TCZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TEZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TFZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9		85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TRZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	スイング 形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TCSZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TESZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK3027TFSZ	75,000	87.2	9.5	90.0%	A 重油	6.6～9.9	静音形	85.4%	10.0	85.6%	10.0	85.8%	10.0
			HK4027TCZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TEZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TFZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2		85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TR5Z	100,000	116	12.7	90.0%	A 重油	9.9～13.2	スイング 形,50Hz	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TR6Z	100,000	116	12.7	90.0%	A 重油	9.9～13.2	スイング 形,60Hz	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TCSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TESZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TFSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK4027TRSZ	100,000	116	12.7	90.0%	A 重油	9.9～13.2	静音形	85.4%	13.3	85.6%	13.3	85.8%	13.3
			HK5027TCZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5027TEZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5027TFZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5		85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5027TCSZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5027TESZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK5027TFSZ	125,000	145	15.8	90.0%	A 重油	13.2～16.5	静音形	85.4%	16.7	85.6%	16.6	85.8%	16.6
			HK6027TCZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6027TEZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6027TFZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8		85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6027TCSZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6027TESZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
			HK6027TFSZ	150,000	174	19.0	90.0%	A 重油	16.5～19.8	静音形	85.4%	20.0	85.6%	20.0	85.8%	19.9
現行機種HK30・29型（機器熱効率 90% ）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											5.1%		4.9%		4.6%	

※1 製造年度を使用開始年度とみなし、毎年一定の使用期間がある場合の経年変化目安とする