

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量 ※1																							
				(kcal/h)	(kW)						1987		1988		1989		1990		1991		1992		1993		1994		1995							
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)						
11型 ・ 15型 ・ 20型	1987 (S62)	1995 (H7)	HK1520SC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK1520SE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK1520TC	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK1520TE	38,000	44.2	4.8	90.0%	A重油	3.3～4.95		81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK1520TCP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形	81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK1520TEP	38,000	44.2	4.8	90.0%	A重油	3.3～4.95	静音形	81.5%	5.3	81.7%	5.3	81.9%	5.3	82.1%	5.3	82.3%	5.3	82.5%	5.2	82.8%	5.2	83.0%	5.2	83.2%	5.2						
			HK2020SC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020SE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TC	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TE	50,000	58.1	6.4	90.0%	A重油	4.95～6.0		81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TCP	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TEP	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TCS	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK2020TES	50,000	58.1	6.4	90.0%	A重油	4.95～6.0	静音形	81.5%	7.0	81.7%	7.0	81.9%	7.0	82.1%	6.9	82.3%	6.9	82.5%	6.9	82.8%	6.9	83.0%	6.9	83.2%	6.9						
			HK3015TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3015TF	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020SC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020SE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TC	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TF	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TCP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TEP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TFP	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TCS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TES	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TFS	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TCD	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TED	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3020TFD	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	デラックス形	81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK3011TCE	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		81.5%	10.5	81.7%	10.5	81.9%	10.4	82.1%	10.4	82.3%	10.4	82.5%	10.4	82.8%	10.3	83.0%	10.3	83.2%	10.3						
			HK4015TC	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4015TF	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TC	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TE	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TF	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TF	87,000	101	11.0	90.0%	A重油	9.9～13.2		81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TCP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TEP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TFP	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TCS	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TES	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
			HK4020TFS	87,000	101	11.0	90.0%	A重油	9.9～13.2	静音形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9						
HK4020TCD	87,000	101	11.0	90.0%	A重油	9.9～13.2	デラックス形	81.5%	12.2	81.7%	12.1	81.9%	12.1	82.1%	12.1	82.3%	12.0	82.5%	12.0	82.8%	12.0	83.0%	12.0	83.2%	11.9									
HK4020TED	87,000	10																																