

ネポン株式会社

【ハウスカオンキ 25Z型シリーズ】 2026 年度 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量 ※1																			
											1997		1998		1999		2000		2001		2002		2003		2004		2005			
				(kcal/h)	(kW)						%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング 形	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9		83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	スイング 形	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6～9.9	静音形	83.6%	10.2	83.9%	10.2	84.1%	10.2	84.3%	10.1	84.5%	10.1	84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0		
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9～13.2		83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TR5Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング 形,50Hz	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9～13.2	スイング 形,60Hz	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9～13.2	静音形	83.6%	13.6	83.9%	13.6	84.1%	13.6	84.3%	13.5	84.5%	13.5	84.7%	13.5	85.0%	13.4	85.2%	13.4	85.4%	13.3		
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2～16.5		83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2～16.5	静音形	83.6%	17.0	83.9%	17.0	84.1%	16.9	84.3%	16.9	84.5%	16.9	84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7		
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
			HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
			HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5～19.8		83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
			HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
			HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
			HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5～19.8	静音形	83.6%	20.4	83.9%	20.4	84.1%	20.3	84.3%	20.3	84.5%	20.2	84.7%	20.2	85.0%	20.1	85.2%	20.1	85.4%	20.0		
現行機種HK30・29型（機器熱効率 90% ）へ設備更新した場合の 経年変化節減率 ※同等熱出力換算											7.1%		6.8%		6.6%		6.3%		6.1%		5.8%		5.6%		5.4%		5.1%			

※1 製造年度を使用開始年度とみなし、毎年一定の使用期間がある場合の経年変化目安とする